

屋内照明器具特性

品番 (品名)	LGWC47107									
光源	LLD2000LCB1 ×1					531.0 lm				
管理番号	K0176341(0)DR1									
BZ分類	BZ3/0.9/BZ2/4.5/BZ3/6.0/BZ2									

器具効率	68%	天井	80%				70%				50%				30%				0%		
			反射率	壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
				床	10%				10%				10%				10%				0%
上方光束	0%	室指数	照明率 (X0.01)																ZCM		
下方光束	68%																				
保守率	良 中 否 0.63 0.6 0.56	0.6	4.4	3.7	3.2	2.9	4.3	3.6	3.2	2.9	4.2	3.6	3.2	2.9	4.0	3.5	3.2	2.9	2.8		
		0.8	5.1	4.5	4.0	3.7	5.0	4.4	4.0	3.7	4.8	4.3	4.0	3.7	4.7	4.3	3.9	3.7	3.5		
		1.0	5.5	5.0	4.6	4.2	5.4	4.9	4.5	4.2	5.3	4.8	4.5	4.2	5.1	4.7	4.4	4.2	4.1		
		1.25	5.9	5.4	5.0	4.7	5.8	5.3	5.0	4.7	5.6	5.2	4.9	4.7	5.5	5.1	4.9	4.6	4.5		
下方投影面積	c m ²	1.5	6.1	5.7	5.3	5.1	6.0	5.6	5.3	5.0	5.9	5.5	5.2	5.0	5.7	5.4	5.2	5.0	4.8		
		2.0	6.4	6.1	5.8	5.5	6.3	6.0	5.7	5.5	6.2	5.9	5.6	5.4	6.0	5.8	5.6	5.4	5.3		
取付高さ	器具間隔最大限		2.5	6.6	6.3	6.1	5.8	6.5	6.2	6.0	5.8	6.4	6.1	5.9	5.7	6.2	6.0	5.8	5.7	5.5	
	横方向 (A)	縦方向 (B)	3.0	6.7	6.5	6.3	6.1	6.6	6.4	6.2	6.0	6.5	6.3	6.1	5.9	6.3	6.2	6.0	5.9	5.7	
H m	1.17H m	1.17H m	4.0	6.9	6.7	6.5	6.3	6.8	6.6	6.4	6.3	6.6	6.5	6.3	6.2	6.5	6.3	6.2	6.1	6.0	
			5.0	7.0	6.8	6.7	6.5	6.9	6.7	6.6	6.5	6.7	6.6	6.5	6.4	6.6	6.5	6.4	6.3	6.1	
			7.0	7.1	7.0	6.8	6.7	7.0	6.9	6.8	6.7	6.8	6.7	6.7	6.6	6.7	6.6	6.5	6.5	6.3	
			10.0	7.2	7.1	7.0	6.9	7.1	7.0	6.9	6.8	6.9	6.8	6.8	6.7	6.8	6.7	6.7	6.6	6.4	

