

# 屋内照明器具特性

品番 (品名)	LGB10780	
光源	LED6200_70_1125 x1 1125.0 lm	
管理番号	K0157912(0)DB1	
BZ分類	BZ4/6.0/BZ5	

器具効率	100%	天井	80%				70%				50%				30%				0%																																				
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%																																				
		床	10%				10%				10%				10%				0%																																				
上方光束	8%	室指数																		照明率 (X0.01)																		ZCM																	
下方光束	92%																																																						
保守率	良 中 否	0.63	0.6	0.56	0.6	59	48	41	36	57	47	40	35	54	45	39	35	52	44	38	34	32																																	
		0.6	0.6	0.6	0.6	69	58	51	46	67	57	50	45	63	55	49	45	60	53	48	44	41																																	
		0.56	0.56	0.56	0.56	75	65	58	53	73	64	57	52	69	62	56	51	66	59	54	50	47																																	
		0.56	0.56	0.56	0.56	81	72	65	60	78	70	64	59	74	68	62	58	71	65	61	57	54																																	
下方投影面積	c m <sup>2</sup>	1.25	1.5	2.0	2.5	81	72	65	60	78	70	64	59	74	68	62	58	71	65	61	57	54																																	
		1.5	2.0	2.5	3.0	84	76	70	65	82	75	69	64	78	72	67	63	74	69	65	61	58																																	
等価発光面積	c m <sup>2</sup>	2.0	2.5	3.0	4.0	89	83	77	73	87	81	76	72	83	78	73	70	79	75	71	68	64																																	
		2.5	3.0	4.0	5.0	92	87	82	78	90	85	80	77	86	82	78	74	82	78	75	72	68																																	
取付高さ	器具間隔最大限		2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20																																		
	横方向 (A)	縦方向 (B)																																																					
1.5m	2.13m	1.49m	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20																																		
2	2.83	1.67	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20																																		
2.5	3.53	2.48	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20																																		
3	4.24	2.8	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20																																		

