

# 屋内照明器具特性

品番 (品名)	XY2890K																
光源	LDA4L-H-E17/E/S/W/2 ×1 440.0 lm																
管理番号	K0176847(2)DR1																
BZ分類	BZ10																

器具効率	59%	天井	80%				70%				50%				30%				0%		
			反射率	壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
				床	10%				10%				10%				10%				0%
上方光束	27%	室指数	照明率 (X0.01) ZCM																		
下方光束	32%																				
保守率	良 中 否 0.63 0.6 0.56	0.6	2.5	1.7	1.2	0.8	2.2	1.5	1.1	0.8	1.8	1.3	0.9	0.6	1.4	1.0	0.7	0.4	0.1		
		0.8	2.9	2.1	1.6	1.2	2.7	2.0	1.5	1.1	2.2	1.6	1.2	0.9	1.7	1.3	1.0	0.7	0.3		
		1.0	3.3	2.5	2.0	1.6	3.0	2.3	1.8	1.4	2.4	1.9	1.5	1.2	1.9	1.5	1.2	0.9	0.5		
		1.25	3.6	2.9	2.3	1.9	3.3	2.6	2.1	1.8	2.7	2.2	1.8	1.5	2.1	1.7	1.4	1.2	0.6		
下方投影面積	cm <sup>2</sup>	1.5	3.8	3.2	2.6	2.2	3.5	2.9	2.4	2.0	2.9	2.4	2.0	1.7	2.3	1.9	1.6	1.4	0.8		
		2.0	4.2	3.6	3.1	2.7	3.8	3.3	2.9	2.5	3.2	2.8	2.4	2.1	2.6	2.2	2.0	1.7	1.1		
取付高さ	器具間隔最大限		2.5	4.4	3.9	3.4	3.0	4.1	3.6	3.2	2.8	3.4	3.0	2.7	2.4	2.8	2.5	2.2	2.0	1.3	
	横方向 (A)	縦方向 (B)	3.0	4.6	4.1	3.7	3.3	4.2	3.8	3.4	3.1	3.5	3.2	2.9	2.6	2.9	2.6	2.4	2.2	1.4	
Hm	0.00Hm	0.00Hm	4.0	4.8	4.4	4.0	3.7	4.5	4.1	3.8	3.5	3.8	3.5	3.2	3.0	3.1	2.9	2.7	2.5	1.7	
			5.0	5.0	4.6	4.3	4.0	4.6	4.3	4.0	3.7	3.9	3.6	3.4	3.2	3.2	3.0	2.8	2.7	1.9	
			7.0	5.1	4.9	4.6	4.4	4.8	4.5	4.3	4.1	4.1	3.9	3.7	3.5	3.4	3.2	3.1	3.0	2.1	
			10.0	5.3	5.1	4.9	4.7	4.9	4.7	4.6	4.4	4.2	4.1	3.9	3.8	3.6	3.4	3.3	3.2	2.3	

