

屋内照明器具特性	
品番 (品名)	NNF W2 1 8 0 0 K
光源	LED5000_85_990 x1 990.0 l m
管理番号	K0175591 ( 0 ) DR 1
B Z 分類	BZ6 / 1.4 / BZ5 / 2.3 / BZ6

器具効率	100 %	天井	80 %				70 %				50 %				30 %				0 %	
	上方光束 20 %		反射率	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
下方光束	80 %	床		10 %				10 %				10 %				10 %				0 %
室指数	照明率 ( X0.01 )																			ZCM
保守率	良	0.83	0.6	52	39	31	26	49	38	30	25	45	35	29	24	41	33	27	23	19
	中	0.81	0.8	61	49	41	35	58	47	40	34	53	44	37	32	48	41	35	31	27
	否	0.77	1.0	67	56	48	42	64	54	46	41	59	50	44	39	54	46	41	37	32
			1.25	73	63	55	49	70	60	53	47	64	56	50	45	58	52	47	43	38
下方投影面積	c m <sup>2</sup>		1.5	77	68	60	54	74	65	58	53	68	60	55	50	62	56	51	47	42
等価発光面積	c m <sup>2</sup>		2.0	83	75	68	62	79	72	66	61	73	67	62	57	67	62	58	54	48
取付高さ	器具間隔最大限		2.5	86	79	73	68	83	76	71	66	76	71	67	62	70	66	62	59	52
	横方向 (A)	縦方向 (B)																		
1.5m	2.13 m	1.92 m	3.0	89	83	77	72	86	80	75	70	79	74	70	66	73	69	66	63	56
2	2.84	2.54	4.0	92	87	83	78	89	84	80	76	82	78	75	72	76	73	70	68	60
2.5	3.57	3.16	5.0	94	90	86	82	91	87	83	80	84	81	78	75	78	75	73	71	63
3	4.26	3.78	7.0	97	93	90	87	93	90	88	85	87	84	82	80	81	79	77	75	67
			10.0	99	96	94	92	95	93	91	89	89	87	85	84	83	81	80	78	70

