

屋内照明器具特性	
品番 (品名)	NNFS 21870C
光源	LED3000_85_1390 x1 1390.0 lm
管理番号	K0175588(0)DR1
BZ分類	BZ6/1.1/BZ5/3.5/BZ6/4.5/BZ5/6.0/BZ6

器具効率	100%	天井	80%				70%				50%				30%				0%			
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%			
上方光束	19%	床	10%				10%				10%				10%				0%			
下方光束	81%	室指数	照明率 (X0.01) ZCM																			
保守率	良	0.83	0.6	52	39	31	26	49	38	30	25	45	35	29	24	41	33	27	23	20		
	中	0.81	0.8	61	49	41	35	58	47	40	34	53	44	37	32	49	41	35	31	27		
	否	0.77	1.0	67	56	48	42	64	54	47	41	59	50	44	39	54	47	41	37	32		
			1.25	73	63	55	49	70	61	53	48	64	56	50	45	59	52	47	43	38		
下方投影面積	c m ²		1.5	77	68	60	54	74	65	58	53	68	61	55	50	62	56	52	47	42		
	等価発光面積		c m ²	2.0	83	75	68	63	80	72	66	61	73	67	62	58	67	62	58	54	48	
取付高さ	器具間隔最大限		2.5	87	79	73	68	83	77	71	66	77	71	67	63	71	66	63	59	53		
	横方向 (A)	縦方向 (B)	3.0	89	83	77	73	86	80	75	71	79	75	70	67	73	69	66	63	56		
1.5m	2.15m	1.93m	4.0	92	87	83	79	89	84	80	76	83	79	75	72	76	73	70	68	61		
2	2.86	2.54	5.0	95	90	86	83	91	87	84	80	85	81	78	76	78	76	73	71	64		
2.5	3.59	3.16	7.0	97	94	91	88	94	91	88	85	87	85	82	80	81	79	77	75	68		
3	4.28	3.76	10.0	99	96	94	92	96	93	91	89	89	87	85	84	83	82	80	79	71		

