

# 屋内照明器具特性

品番 (品名)	NWCF 11505C														
光源	LED5000_85_595 x1 595.0 l m														
管理番号	K0168033(0)DR1														
BZ分類	BZ5														

器具効率	100 %	天井	80 %				70 %				50 %				30 %				0 %	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %	
		床	10 %				10 %				10 %				10 %				0 %	
上方光束	2 %																			
下方光束	98 %																			
室指数	照明率 ( X0.01 ) ZCM																			
保守率	良	0.83	0.6	55	43	35	29	54	42	34	29	51	41	34	29	49	40	33	29	26
	中	0.81	0.8	65	53	45	39	63	52	45	39	60	51	44	39	58	49	43	38	36
	否	0.77	1.0	72	61	53	46	70	60	52	46	67	58	51	46	64	56	50	45	43
			1.25	78	67	60	54	76	66	59	53	72	64	58	53	69	62	57	52	49
下方投影面積	cm <sup>2</sup>		1.5	82	72	65	59	80	71	64	59	76	69	63	58	73	67	62	57	54
等価発光面積	cm <sup>2</sup>		2.0	87	79	73	68	85	78	72	67	82	76	70	66	79	73	69	65	62
取付高さ	器具間隔最大限		2.5	91	84	78	73	89	83	77	73	86	80	75	71	82	78	74	70	67
	横方向 (A)	縦方向 (B)	3.0	94	87	82	78	92	86	81	77	88	83	79	75	85	81	77	74	71
H m	1.29 H m	1.29 H m	4.0	97	92	87	84	95	90	86	83	92	88	84	81	88	85	82	79	76
			5.0	99	95	91	87	97	93	90	87	94	90	87	85	90	88	85	83	80
			7.0	101	98	95	92	99	97	94	91	96	94	91	89	93	91	89	87	84
			10.0	103	101	98	96	101	99	97	95	98	96	95	93	95	94	92	91	87

