

# 屋内照明器具特性

|         |                |          |
|---------|----------------|----------|
| 品番 (品名) | XLGE5012       |          |
| 光源      | LLD4000VCE1 ×1 | 845.0 lm |
| 管理番号    | K0181592(0)DR1 |          |
| BZ分類    | BZ5            |          |

|                |                    |                    |      |      |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |
|----------------|--------------------|--------------------|------|------|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|
| 器具効率           | 83%                | 天井                 | 80%  |      |     |     | 70% |     |     |     | 50% |     |     |     | 30% |     |     |     | 0%  |     |     |
|                | 上方光束               |                    | 13%  | 反射率  | 70  | 50  | 30  | 10  | 70  | 50  | 30  | 10  | 70  | 50  | 30  | 10  | 70  | 50  | 30  | 10  | 0%  |
|                | 下方光束               |                    | 70%  |      | 床   | 10% |     |     |     | 10% |     |     |     | 10% |     |     |     | 10% |     |     |     |
| 室指数            | 照明率 (X0.01)        |                    |      |      |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     | ZCM |     |
| 保守率            | 良                  | 0.63               | 0.6  | 4.4  | 3.4 | 2.7 | 2.3 | 4.2 | 3.3 | 2.7 | 2.2 | 3.9 | 3.1 | 2.5 | 2.2 | 3.6 | 2.9 | 2.4 | 2.1 | 1.8 |     |
|                | 中                  | 0.6                | 0.8  | 5.2  | 4.2 | 3.5 | 3.1 | 5.0 | 4.1 | 3.5 | 3.0 | 4.6 | 3.9 | 3.3 | 2.9 | 4.3 | 3.6 | 3.2 | 2.8 | 2.5 |     |
|                | 否                  | 0.56               | 1.0  | 5.7  | 4.8 | 4.1 | 3.7 | 5.5 | 4.7 | 4.0 | 3.6 | 5.1 | 4.4 | 3.9 | 3.4 | 4.7 | 4.1 | 3.7 | 3.3 | 3.0 |     |
|                | 下方投影面積             | c m <sup>2</sup>   |      | 1.25 | 6.2 | 5.4 | 4.7 | 4.2 | 6.0 | 5.2 | 4.6 | 4.2 | 5.5 | 4.9 | 4.4 | 4.0 | 5.1 | 4.6 | 4.2 | 3.8 | 3.5 |
| 取付高さ           | 器具間隔最大限            |                    | 1.5  | 6.5  | 5.8 | 5.2 | 4.7 | 6.3 | 5.6 | 5.1 | 4.6 | 5.9 | 5.3 | 4.8 | 4.4 | 5.4 | 5.0 | 4.6 | 4.2 | 3.8 |     |
|                | 横方向 (A)            | 縦方向 (B)            | 2.0  | 7.0  | 6.4 | 5.8 | 5.4 | 6.8 | 6.2 | 5.7 | 5.3 | 6.3 | 5.8 | 5.4 | 5.0 | 5.9 | 5.5 | 5.1 | 4.8 | 4.4 |     |
| H <sub>m</sub> | 1.30H <sub>m</sub> | 1.30H <sub>m</sub> | 2.5  | 7.3  | 6.7 | 6.3 | 5.9 | 7.1 | 6.5 | 6.1 | 5.7 | 6.6 | 6.2 | 5.8 | 5.5 | 6.1 | 5.8 | 5.5 | 5.2 | 4.8 |     |
|                |                    |                    | 3.0  | 7.5  | 7.0 | 6.6 | 6.2 | 7.3 | 6.8 | 6.4 | 6.1 | 6.8 | 6.4 | 6.1 | 5.8 | 6.3 | 6.0 | 5.8 | 5.5 | 5.0 |     |
|                |                    |                    | 4.0  | 7.8  | 7.4 | 7.0 | 6.7 | 7.5 | 7.2 | 6.8 | 6.5 | 7.1 | 6.8 | 6.5 | 6.2 | 6.6 | 6.4 | 6.1 | 5.9 | 5.4 |     |
|                |                    |                    | 5.0  | 7.9  | 7.6 | 7.3 | 7.0 | 7.7 | 7.4 | 7.1 | 6.9 | 7.2 | 7.0 | 6.7 | 6.5 | 6.8 | 6.6 | 6.4 | 6.2 | 5.7 |     |
|                |                    |                    | 7.0  | 8.1  | 7.9 | 7.6 | 7.4 | 7.9 | 7.7 | 7.4 | 7.2 | 7.4 | 7.2 | 7.1 | 6.9 | 7.0 | 6.8 | 6.7 | 6.5 | 6.0 |     |
|                |                    |                    | 10.0 | 8.3  | 8.1 | 7.9 | 7.8 | 8.0 | 7.9 | 7.7 | 7.6 | 7.6 | 7.4 | 7.3 | 7.2 | 7.1 | 7.0 | 6.9 | 6.8 | 6.2 |     |

