

屋内照明器具特性

品番 (品名)	XLGE5116				
光源	LLD4000NCE1 ×1 845.0 l m				
管理番号	K0181605 (0) DR 1				
BZ分類	BZ5 / 0.9 / BZ4 / 6.0 / BZ5 / 8.5 / BZ4				

器具効率	60 %	天井	80 %				70 %				50 %				30 %				0 %		
			反射率	壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
				床	10 %				10 %				10 %				10 %				0 %
上方光束	0 %	室指数	照明率 (X0.01)																ZCM		
下方光束	60 %																				
保守率	良 中 否 0.63 0.6 0.56	0.6	3.4	2.7	2.3	1.9	3.4	2.7	2.2	1.9	3.2	2.6	2.2	1.9	3.1	2.6	2.2	1.9	1.8		
		0.8	4.0	3.4	2.9	2.6	3.9	3.3	2.9	2.6	3.8	3.2	2.8	2.5	3.6	3.2	2.8	2.5	2.4		
		1.0	4.4	3.8	3.4	3.0	4.3	3.8	3.3	3.0	4.2	3.7	3.3	3.0	4.0	3.6	3.2	3.0	2.8		
		1.25	4.8	4.2	3.8	3.5	4.7	4.2	3.8	3.4	4.5	4.1	3.7	3.4	4.3	4.0	3.6	3.4	3.3		
下方投影面積	c m ²	1.5	5.0	4.5	4.1	3.8	4.9	4.5	4.1	3.8	4.7	4.3	4.0	3.7	4.6	4.2	3.9	3.7	3.6		
		2.0	5.4	4.9	4.6	4.3	5.3	4.9	4.5	4.3	5.1	4.7	4.5	4.2	4.9	4.6	4.4	4.2	4.0		
取付高さ	器具間隔最大限		2.5	5.6	5.2	4.9	4.6	5.5	5.1	4.8	4.6	5.3	5.0	4.8	4.5	5.1	4.9	4.7	4.5	4.3	
	横方向 (A)	縦方向 (B)	3.0	5.7	5.4	5.1	4.9	5.6	5.3	5.1	4.8	5.4	5.2	5.0	4.8	5.3	5.1	4.9	4.7	4.6	
H m	1.22 H m	1.22 H m	4.0	5.9	5.6	5.4	5.2	5.8	5.6	5.4	5.2	5.6	5.4	5.3	5.1	5.5	5.3	5.2	5.0	4.9	
			5.0	6.0	5.8	5.6	5.4	5.9	5.7	5.5	5.4	5.8	5.6	5.4	5.3	5.6	5.5	5.3	5.2	5.1	
			7.0	6.1	6.0	5.8	5.7	6.0	5.9	5.8	5.6	5.9	5.8	5.7	5.6	5.7	5.6	5.5	5.5	5.3	
			10.0	6.2	6.1	6.0	5.9	6.1	6.0	5.9	5.9	6.0	5.9	5.8	5.7	5.9	5.8	5.7	5.6	5.5	

