

屋内照明器具特性

品番 (品名)	LGC45826														
光源	LED6500_70_4090 x1 4090.0 1m														
管理番号	K0182162(0)DB1														
BZ分類	BZ5														

器具効率	100%	天井	80%				70%				50%				30%				0%		
			反射率	壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
				床	10%				10%				10%				10%				0%
上方光束 下方光束	11% 89%	室指数	照明率 (X0.01) ZCM																		
保守率	良 中 否 0.63 0.6 0.56	0.6	5.5	4.3	3.5	3.0	5.3	4.2	3.4	2.9	5.0	4.0	3.3	2.9	4.6	3.8	3.2	2.8	2.5		
		0.8	6.4	5.3	4.5	3.9	6.2	5.2	4.4	3.9	5.8	4.9	4.3	3.8	5.5	4.7	4.1	3.7	3.4		
		1.0	7.1	6.0	5.2	4.7	6.9	5.9	5.1	4.6	6.4	5.6	4.9	4.5	6.0	5.3	4.8	4.3	4.0		
		1.25	7.7	6.7	5.9	5.4	7.4	6.5	5.8	5.3	7.0	6.2	5.6	5.1	6.5	5.9	5.4	5.0	4.6		
下方投影面積 等価発光面積	c m ² c m ²	1.5	8.1	7.2	6.5	5.9	7.8	7.0	6.3	5.8	7.3	6.6	6.1	5.6	6.9	6.3	5.8	5.4	5.0		
		2.0	8.6	7.9	7.2	6.7	8.4	7.7	7.1	6.6	7.9	7.3	6.8	6.4	7.4	6.9	6.5	6.1	5.7		
取付高さ	器具間隔最大限		2.5	9.0	8.3	7.7	7.3	8.7	8.1	7.6	7.1	8.2	7.7	7.3	6.9	7.7	7.3	7.0	6.6	6.2	
	横方向 (A)	縦方向 (B)	3.0	9.2	8.6	8.1	7.7	8.9	8.4	7.9	7.5	8.4	8.0	7.6	7.3	8.0	7.6	7.3	7.0	6.5	
1.5m	1.93m	1.94m	4.0	9.5	9.1	8.6	8.3	9.3	8.8	8.4	8.1	8.8	8.4	8.1	7.8	8.3	8.0	7.7	7.5	7.0	
2	2.55	2.55	5.0	9.7	9.3	9.0	8.6	9.5	9.1	8.8	8.5	9.0	8.7	8.4	8.1	8.5	8.3	8.0	7.8	7.3	
2.5	3.18	3.19	7.0	9.9	9.6	9.4	9.1	9.7	9.4	9.2	8.9	9.2	9.0	8.8	8.6	8.7	8.6	8.4	8.2	7.7	
3	3.79	3.8	10.0	10.1	9.9	9.7	9.5	9.9	9.7	9.5	9.3	9.4	9.2	9.1	8.9	8.9	8.8	8.7	8.5	8.0	

