

屋内照明器具特性	
品番 (品名)	LGC51142K
光源	LED6200_70_5300 x1 5300.0lm
管理番号	K0183805(0)D 1
BZ分類	BZ5

器具効率	100%	天井	80%				70%				50%				30%				0%	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%	
上方光束	6%	床	10%				10%				10%				10%				0%	
下方光束	94%	室指数	照明率 (X0.01)																ZCM	
保守率	良 0.63 中 0.6 否 0.56	0.6	55	43	35	30	54	42	35	29	51	40	34	29	48	39	33	28	26	
		0.8	65	53	45	40	63	52	45	39	60	50	44	38	56	48	42	38	35	
		1.0	71	61	53	47	69	59	52	46	66	57	50	45	62	55	49	45	42	
		1.25	77	67	60	54	75	66	59	53	71	63	57	52	67	61	56	51	48	
下方投影面積	c m ²	1.5	81	72	65	60	79	71	64	59	75	68	62	58	71	65	60	56	53	
		2.0	87	79	73	68	85	78	72	67	81	75	70	65	77	72	67	64	60	
取付高さ	器具間隔最大限		2.5	91	84	78	73	88	82	77	72	84	79	74	71	80	76	72	69	65
	横方向 (A)	縦方向 (B)	3.0	93	87	82	78	91	85	81	77	87	82	78	75	83	79	76	73	69
H m	1.27 H m	1.27 H m	4.0	96	91	87	83	94	90	86	82	90	86	83	80	86	83	80	78	74
			5.0	98	94	91	87	96	92	89	86	92	89	86	83	88	86	83	81	77
			7.0	100	97	95	92	98	96	93	91	94	92	90	88	91	89	87	85	81
			10.0	102	100	98	96	100	98	96	94	96	95	93	91	93	91	90	89	84

