

屋内照明器具特性

品番 (品名)	LGC51151K														
光源	LED6200_70_4800 x1 4800.0 lm														
管理番号	K0168770(0)DB1														
BZ分類	BZ5														

器具効率	100%	天井	80%				70%				50%				30%				0%		
			反射率	壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
				床	10%				10%				10%				10%				0%
上方光束	6%	室指数																			
下方光束	94%	照明率 (X0.01)																			
保守率	良 0.63 中 0.6 否 0.56	0.6	57	45	37	32	55	44	37	32	52	42	36	31	50	41	35	31	28		
		0.8	67	55	48	42	65	54	47	42	61	52	46	41	58	51	45	40	38		
下方投影面積	c m ²	1.25	79	69	62	57	77	68	61	56	73	66	60	55	70	63	58	54	51		
		1.5	83	74	68	62	81	73	67	62	77	70	65	60	73	68	63	59	56		
等価発光面積	c m ²	2.0	88	81	75	70	86	80	74	70	82	77	72	68	79	74	70	67	63		
		2.5	92	86	80	76	90	84	79	75	86	81	77	73	82	78	75	72	68		
取付高さ	器具間隔最大限		3.0	94	89	84	80	92	87	83	79	88	84	80	77	85	81	78	75	72	
	横方向 (A)	縦方向 (B)	4.0	97	93	89	86	95	91	88	85	91	88	85	82	88	85	83	80	76	
H m	1.21H m	1.21H m	5.0	99	96	92	89	97	94	91	88	93	91	88	86	90	88	85	83	79	
			7.0	101	99	96	94	99	97	95	92	96	94	92	90	92	90	89	87	83	
			10.0	103	101	99	97	101	99	98	96	97	96	94	93	94	93	92	90	86	

