

屋内照明器具特性

品番 (品名) **LGB15489**

光源 **LLD3020CU1 ×1** **615.0 lm**

管理番号 **K0185503(0)DR1**

BZ分類 **BZ1**

| 器具効率 | 76% | 天井 | 80% | | | | 70% | | | | 50% | | | | 30% | | | | 0% | |
|--------|-----------------|---------|-------------|-----|----|----|-----|-----|----|----|-----|-----|----|----|-----|-----|----|----|-----|----|
| | | | 70 | 50 | 30 | 10 | 70 | 50 | 30 | 10 | 70 | 50 | 30 | 10 | 70 | 50 | 30 | 10 | | |
| 上方光束 | 0% | 反射率 | 壁 | 10% | | | | 10% | | | | 10% | | | | 10% | | | | 0% |
| 下方光束 | 76% | | 床 | 10% | | | | 10% | | | | 10% | | | | 10% | | | | 0% |
| | | 室指数 | 照明率 (X0.01) | | | | | | | | | | | | | | | | ZCM | |
| 保守率 | 良 0.67 | 0.6 | 64 | 59 | 56 | 54 | 63 | 59 | 56 | 54 | 62 | 58 | 56 | 54 | 61 | 58 | 56 | 54 | 53 | |
| | 中 0.63 | 0.8 | 68 | 64 | 61 | 59 | 68 | 64 | 61 | 59 | 67 | 63 | 61 | 59 | 66 | 63 | 61 | 59 | 58 | |
| | 否 0.56 | 1.0 | 71 | 68 | 65 | 63 | 71 | 67 | 65 | 63 | 69 | 66 | 64 | 62 | 68 | 66 | 64 | 62 | 61 | |
| 下方投影面積 | cm ² | 1.25 | 74 | 70 | 68 | 66 | 73 | 70 | 68 | 66 | 72 | 69 | 67 | 65 | 70 | 68 | 66 | 65 | 64 | |
| | | 1.5 | 75 | 72 | 70 | 68 | 74 | 72 | 70 | 68 | 73 | 71 | 69 | 67 | 72 | 70 | 68 | 67 | 66 | |
| 等価発光面積 | cm ² | 2.0 | 77 | 75 | 73 | 71 | 76 | 74 | 72 | 71 | 75 | 73 | 71 | 70 | 73 | 72 | 71 | 70 | 68 | |
| | | 2.5 | 78 | 76 | 75 | 73 | 77 | 76 | 74 | 73 | 76 | 74 | 73 | 72 | 74 | 73 | 72 | 71 | 70 | |
| 取付高さ | 器具間隔最大限 | | 3.0 | 79 | 77 | 76 | 74 | 78 | 77 | 75 | 74 | 77 | 75 | 74 | 73 | 75 | 74 | 73 | 72 | 71 |
| | 横方向 (A) | 縦方向 (B) | 4.0 | 80 | 79 | 77 | 76 | 79 | 78 | 77 | 76 | 77 | 76 | 75 | 76 | 75 | 74 | 74 | 72 | |
| Hm | 0.35Hm | 0.35Hm | 5.0 | 80 | 79 | 78 | 77 | 80 | 79 | 78 | 77 | 78 | 77 | 76 | 76 | 76 | 75 | 75 | 73 | |
| | | | 7.0 | 81 | 80 | 80 | 79 | 80 | 79 | 79 | 78 | 79 | 78 | 77 | 77 | 77 | 76 | 76 | 74 | |
| | | | 10.0 | 82 | 81 | 80 | 80 | 81 | 80 | 80 | 79 | 79 | 79 | 78 | 78 | 77 | 77 | 76 | 74 | |

