

屋内照明器具特性

品番 (品名)	XAD5 100 V	
光源	LLD5000VCC1 ×1	1140.0 lm
管理番号	K0187672 (1) DR 1	
BZ分類	BZ3 / 0.7 / BZ2	

器具効率	95 %	天井	80 %				70 %				50 %				30 %				0 %	
	上方光束		0 %	反射率	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10
下方光束	95 %	床	10 %				10 %				10 %				10 %				0 %	
室指数			照明率 (X0.01)																ZCM	
保守率	良	0.67	0.6	62	53	47	42	61	52	47	42	60	52	46	42	58	51	46	42	41
	中	0.63	0.8	72	64	58	54	71	63	57	53	69	62	57	53	67	61	56	53	51
	否	0.56	1.0	78	71	65	61	77	70	65	61	75	69	64	61	73	67	63	60	58
			1.25	83	77	72	68	82	76	71	67	80	74	70	67	78	73	69	67	65
下方投影面積	cm ²		1.5	86	81	76	72	85	80	75	72	83	78	74	71	81	77	74	71	69
	等価発光面積		2.0	91	86	82	79	89	85	81	78	87	83	80	77	85	82	79	77	75
取付高さ	器具間隔最大限		2.5	93	89	86	83	92	88	85	82	89	86	84	81	87	85	82	80	78
	横方向 (A)	縦方向 (B)	3.0	95	91	88	86	93	90	88	85	91	88	86	84	89	87	85	83	81
Hm	1.24 Hm	1.24 Hm	4.0	97	94	92	89	96	93	91	89	93	91	89	88	91	89	88	86	84
			5.0	98	96	94	92	97	95	93	91	94	93	91	90	92	91	90	88	86
			7.0	99	98	96	95	98	97	95	94	96	95	93	92	94	93	92	91	88
			10.0	100	99	98	97	99	98	97	96	97	96	95	94	95	94	93	93	90

