

屋内照明器具特性

品番 (品名)	XAD5 1 6 1 L	
光源	LLD5010LCC1 ×1	1095.0 1 m
管理番号	K0187676 (2) DR 1	
BZ分類	BZ1	

器具効率	81 %	天井	80 %				70 %				50 %				30 %				0 %	
	上方光束 0 %		反射率	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
下方光束	81 %	床		10 %				10 %				10 %				10 %				0 %
室指数	照明率 (X0.01)																			ZCM
保守率	良	0.67	0.6	70	65	62	61	69	65	62	60	68	65	62	60	67	64	62	60	59
	中	0.63	0.8	74	70	67	65	73	70	67	65	72	69	67	65	71	68	66	65	64
	否	0.56	1.0	77	73	71	69	76	73	70	68	75	72	70	68	74	71	69	68	67
下方投影面積 等価発光面積	c m ²	1.25	79	76	73	72	78	75	73	71	77	74	72	71	76	74	72	71	69	
		1.5	80	78	75	74	80	77	75	73	78	76	74	73	77	75	74	72	71	
取付高さ	器具間隔最大限		2.0	82	80	78	77	82	79	78	76	80	78	77	75	79	77	76	75	
	横方向 (A)	縦方向 (B)	2.5	83	81	80	78	83	81	79	78	81	80	78	77	80	78	77	76	
H m	0.80 H m	0.80 H m	3.0	84	83	81	80	83	82	80	79	82	80	79	78	80	79	78	77	
			4.0	85	84	83	82	84	83	82	81	83	82	81	80	81	80	79	77	
			5.0	86	85	84	83	85	84	83	82	83	82	82	81	81	81	80	78	
			7.0	86	86	85	84	85	85	84	83	84	83	83	82	82	82	81	79	
			10.0	87	86	86	85	86	85	85	84	84	84	83	83	82	82	82	79	

