

屋内照明器具特性	
品番 (品名)	XAD3 108 L
光源	LLD4000LCE1 ×1                      845.0 l m
管理番号	K0187668 (1) DR 1
BZ分類	BZ2 / 1.8 / BZ3

器具効率	66 %	天井	80 %				70 %				50 %				30 %				0 %		
	上方光束 0 %		反射率	壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
				床	10 %				10 %				10 %				10 %				0 %
下方光束 66 %		室指数	照明率 ( X0.01)																ZCM		
保守率	良 0.67	0.6	4.4	3.7	3.3	3.0	4.3	3.7	3.3	3.0	4.2	3.6	3.3	3.0	4.1	3.6	3.2	3.0	2.9		
	中 0.63	0.8	5.0	4.4	4.0	3.7	4.9	4.4	4.0	3.7	4.8	4.3	3.9	3.7	4.7	4.2	3.9	3.7	3.5		
	否 0.56	1.0	5.4	4.9	4.5	4.2	5.3	4.8	4.4	4.2	5.2	4.7	4.4	4.1	5.0	4.6	4.4	4.1	4.0		
		1.25	5.7	5.3	4.9	4.6	5.7	5.2	4.9	4.6	5.5	5.1	4.8	4.6	5.3	5.0	4.7	4.5	4.4		
下方投影面積	c m <sup>2</sup>	1.5	6.0	5.5	5.2	4.9	5.9	5.5	5.2	4.9	5.7	5.4	5.1	4.9	5.6	5.3	5.0	4.8	4.7		
		2.0	6.3	5.9	5.6	5.4	6.2	5.8	5.6	5.3	6.0	5.7	5.5	5.3	5.8	5.6	5.4	5.2	5.1		
取付高さ	器具間隔最大限		2.5	6.4	6.1	5.9	5.7	6.3	6.1	5.8	5.6	6.2	5.9	5.7	5.6	6.0	5.8	5.6	5.5	5.3	
	横方向 (A)	縦方向 (B)	3.0	6.6	6.3	6.1	5.9	6.5	6.2	6.0	5.8	6.3	6.1	5.9	5.8	6.1	6.0	5.8	5.7	5.5	
H m	1.14 H m	1.14 H m	4.0	6.7	6.5	6.3	6.2	6.6	6.4	6.3	6.1	6.5	6.3	6.2	6.0	6.3	6.2	6.0	5.9	5.8	
			5.0	6.8	6.6	6.5	6.3	6.7	6.6	6.4	6.3	6.6	6.4	6.3	6.2	6.4	6.3	6.2	6.1	5.9	
			7.0	6.9	6.8	6.7	6.6	6.8	6.7	6.6	6.5	6.7	6.6	6.5	6.4	6.5	6.4	6.4	6.3	6.1	
			10.0	7.0	6.9	6.8	6.7	6.9	6.8	6.7	6.7	6.7	6.7	6.6	6.5	6.6	6.5	6.5	6.4	6.2	

