

屋内照明器具特性

品番 (品名)	XAD3 108 V	
光源	LLD4000VCE1 ×1	845.0 l m
管理番号	K0187668 (1) DR 1	
BZ分類	BZ2 / 1.8 / BZ3	

器具効率	66 %	天井	80 %				70 %				50 %				30 %				0 %	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %	
上方光束	0 %	床	10 %				10 %				10 %				10 %				0 %	
下方光束	66 %	室指数	照明率 (X0.01)																ZCM	
保守率	良 中 否	0.67	0.6	4.4	3.7	3.3	3.0	4.3	3.7	3.3	3.0	4.2	3.6	3.3	3.0	4.1	3.6	3.2	3.0	2.9
		0.63	0.8	5.0	4.4	4.0	3.7	4.9	4.4	4.0	3.7	4.8	4.3	3.9	3.7	4.7	4.2	3.9	3.7	3.5
		0.56	1.0	5.4	4.9	4.5	4.2	5.3	4.8	4.4	4.2	5.2	4.7	4.4	4.1	5.0	4.6	4.4	4.1	4.0
			1.25	5.7	5.3	4.9	4.6	5.7	5.2	4.9	4.6	5.5	5.1	4.8	4.6	5.3	5.0	4.7	4.5	4.4
下方投影面積	c m ²	1.5	6.0	5.5	5.2	4.9	5.9	5.5	5.2	4.9	5.7	5.4	5.1	4.9	5.6	5.3	5.0	4.8	4.7	
		2.0	6.3	5.9	5.6	5.4	6.2	5.8	5.6	5.3	6.0	5.7	5.5	5.3	5.8	5.6	5.4	5.2	5.1	
取付高さ	器具間隔最大限		2.5	6.4	6.1	5.9	5.7	6.3	6.1	5.8	5.6	6.2	5.9	5.7	5.6	6.0	5.8	5.6	5.5	5.3
	横方向 (A)	縦方向 (B)	3.0	6.6	6.3	6.1	5.9	6.5	6.2	6.0	5.8	6.3	6.1	5.9	5.8	6.1	6.0	5.8	5.7	5.5
H m	1.14 H m	1.14 H m	4.0	6.7	6.5	6.3	6.2	6.6	6.4	6.3	6.1	6.5	6.3	6.2	6.0	6.3	6.2	6.0	5.9	5.8
			5.0	6.8	6.6	6.5	6.3	6.7	6.6	6.4	6.3	6.6	6.4	6.3	6.2	6.4	6.3	6.2	6.1	5.9
			7.0	6.9	6.8	6.7	6.6	6.8	6.7	6.6	6.5	6.7	6.6	6.5	6.4	6.5	6.4	6.4	6.3	6.1
			10.0	7.0	6.9	6.8	6.7	6.9	6.8	6.7	6.7	6.7	6.7	6.6	6.5	6.6	6.5	6.5	6.4	6.2

