

屋内照明器具特性	
品番 (品名)	L G W 8 5 0 0 5 B F
光源	LDA4 L - H - E17 / S / 4 × 1 440.0 l m
管理番号	K0186850 (0) DB 1
B Z 分類	BZ9 / 0.9 / BZ8

器具効率	57 %	天井	80 %				70 %				50 %				30 %				0 %	
			壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
上方光束	28 %	床	10 %				10 %				10 %				10 %				0 %	
下方光束	29 %		10 %				10 %				10 %				10 %				0 %	
		室指数	照明率 (X0.01)																Z C M	
保守率	良	0.63	0.6	2.5	1.8	1.4	1.1	2.3	1.7	1.3	1.0	1.9	1.4	1.1	8	1.5	1.1	8	6	3
	中	0.6	0.8	3.0	2.3	1.8	1.5	2.8	2.1	1.7	1.4	2.3	1.8	1.4	1.2	1.8	1.4	1.1	9	5
	否	0.56	1.0	3.4	2.7	2.2	1.8	3.1	2.5	2.0	1.7	2.5	2.0	1.7	1.4	2.0	1.7	1.4	1.2	7
			1.25	3.7	3.0	2.6	2.2	3.4	2.8	2.4	2.0	2.8	2.3	2.0	1.7	2.2	1.9	1.6	1.4	9
下方投影面積		cm ²	1.5	3.9	3.3	2.8	2.5	3.6	3.0	2.6	2.3	2.9	2.5	2.2	1.9	2.4	2.1	1.8	1.6	10
等価発光面積		cm ²	2.0	4.2	3.7	3.3	2.9	3.9	3.4	3.0	2.7	3.2	2.9	2.6	2.3	2.6	2.3	2.1	1.9	1.2
取付高さ	器具間隔最大限		2.5	4.4	4.0	3.6	3.2	4.1	3.7	3.3	3.0	3.4	3.1	2.8	2.6	2.8	2.5	2.3	2.1	1.4
	横方向 (A)	縦方向 (B)	3.0	4.6	4.2	3.8	3.5	4.2	3.8	3.5	3.3	3.5	3.2	3.0	2.8	2.9	2.7	2.5	2.3	1.5
H m	1.67 H m	1.53 H m	4.0	4.8	4.4	4.1	3.9	4.4	4.1	3.8	3.6	3.7	3.5	3.2	3.1	3.0	2.9	2.7	2.5	1.7
			5.0	4.9	4.6	4.3	4.1	4.5	4.3	4.0	3.8	3.8	3.6	3.4	3.3	3.1	3.0	2.8	2.7	1.9
			7.0	5.1	4.8	4.6	4.4	4.7	4.5	4.3	4.1	4.0	3.8	3.7	3.5	3.3	3.2	3.0	2.9	2.1
			10.0	5.2	5.0	4.8	4.7	4.8	4.7	4.5	4.4	4.1	4.0	3.8	3.7	3.4	3.3	3.2	3.1	2.2

