

屋内照明器具特性	
品番 (品名)	L G W8 5 0 8 5 F
光源	LDA4L-H-E17/S/4 ×1 440.0 1 m
管理番号	K0172661(0)DR1
BZ分類	BZ8

器具効率	63%	天井	80%				70%				50%				30%				0%																																				
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%																																				
		床	10%				10%				10%				10%				0%																																				
上方光束	24%	室指数																		照明率 (X0.01)																		ZCM																	
下方光束	39%																																																						
保守率	良 0.63 中 0.6 否 0.56	0.6	2.9	2.0	1.5	1.2	2.6	1.9	1.4	1.1	2.3	1.7	1.3	1.0	1.9	1.4	1.1	0.8	0.6																																				
		0.8	3.4	2.6	2.1	1.7	3.1	2.4	1.9	1.6	2.7	2.1	1.7	1.4	2.3	1.8	1.5	1.2	0.8																																				
		1.0	3.8	3.0	2.4	2.0	3.5	2.8	2.3	1.9	3.0	2.4	2.0	1.7	2.5	2.1	1.7	1.5	1.1																																				
		1.25	4.1	3.4	2.9	2.4	3.8	3.2	2.7	2.3	3.3	2.8	2.4	2.0	2.8	2.4	2.0	1.8	1.3																																				
下方投影面積	c m ²	1.5	4.4	3.7	3.2	2.8	4.1	3.5	3.0	2.6	3.5	3.0	2.6	2.3	3.0	2.6	2.3	2.0	1.5																																				
等価発光面積		c m ²	2.0	4.7	4.1	3.7	3.3	4.4	3.9	3.4	3.1	3.8	3.4	3.0	2.7	3.2	2.9	2.6	2.4	1.8																																			
取付高さ			器具間隔最大限		H m	2.5	5.0	4.4	4.0	3.6	4.6	4.2	3.8	3.4	4.0	3.6	3.3	3.0	3.4	3.1	2.9	2.7	2.0																																
横方向 (A)			縦方向 (B)			3.0	5.1	4.7	4.3	3.9	4.8	4.4	4.0	3.7	4.2	3.8	3.5	3.3	3.6	3.3	3.1	2.9	2.2																																
H m	1.49 H m		1.57 H m	4.0	5.4	5.0	4.6	4.3	5.0	4.7	4.4	4.1	4.4	4.1	3.8	3.6	3.8	3.6	3.4	3.2	2.5																																		
			5.0	5.5	5.2	4.9	4.6	5.2	4.9	4.6	4.3	4.5	4.3	4.1	3.9	3.9	3.7	3.5	3.4	2.6																																			
			7.0	5.7	5.4	5.2	4.9	5.3	5.1	4.9	4.7	4.7	4.5	4.3	4.2	4.1	3.9	3.8	3.7	2.9																																			
			10.0	5.8	5.6	5.4	5.2	5.5	5.3	5.1	5.0	4.8	4.7	4.6	4.4	4.2	4.1	4.0	3.9	3.1																																			

