

|          |                             |
|----------|-----------------------------|
| 屋内照明器具特性 |                             |
| 品番 (品名)  | LGB15050F                   |
| 光源       | LDA4L-H-E17/S/4 ×1 440.0 lm |
| 管理番号     | K0127474(0)DB1              |
| BZ分類     | BZ5/1.8/BZ6                 |

|                |                    |                    |      |    |    |    |     |    |    |    |     |    |    |    |     |    |    |    |    |    |
|----------------|--------------------|--------------------|------|----|----|----|-----|----|----|----|-----|----|----|----|-----|----|----|----|----|----|
| 器具効率           | 82%                | 天井                 | 80%  |    |    |    | 70% |    |    |    | 50% |    |    |    | 30% |    |    |    | 0% |    |
|                | 上方光束               |                    | 15%  | 壁  | 70 | 50 | 30  | 10 | 70 | 50 | 30  | 10 | 70 | 50 | 30  | 10 | 70 | 50 | 30 | 10 |
| 下方光束           | 67%                | 床                  | 10%  |    |    |    | 10% |    |    |    | 10% |    |    |    | 10% |    |    |    | 0% |    |
| 室指数            |                    | 照明率 (X0.01)        | ZCM  |    |    |    |     |    |    |    |     |    |    |    |     |    |    |    |    |    |
| 保守率            | 良                  | 0.67               | 0.6  | 45 | 36 | 30 | 26  | 44 | 35 | 29 | 25  | 40 | 33 | 28 | 24  | 37 | 31 | 26 | 23 | 21 |
|                | 中                  | 0.63               | 0.8  | 52 | 43 | 36 | 32  | 50 | 41 | 35 | 31  | 46 | 39 | 33 | 30  | 42 | 36 | 32 | 28 | 25 |
|                | 否                  | 0.56               | 1.0  | 57 | 48 | 41 | 36  | 54 | 46 | 40 | 35  | 50 | 43 | 38 | 34  | 46 | 40 | 36 | 32 | 29 |
|                |                    |                    | 1.25 | 61 | 52 | 46 | 41  | 58 | 51 | 45 | 40  | 53 | 47 | 42 | 38  | 49 | 44 | 40 | 36 | 32 |
| 下方投影面積         |                    | cm <sup>2</sup>    | 1.5  | 64 | 56 | 50 | 45  | 61 | 54 | 49 | 44  | 56 | 50 | 46 | 42  | 52 | 47 | 43 | 40 | 35 |
| 等価発光面積         |                    | cm <sup>2</sup>    | 2.0  | 68 | 61 | 56 | 51  | 65 | 59 | 54 | 50  | 60 | 55 | 51 | 47  | 55 | 51 | 48 | 45 | 40 |
| 取付高さ           | 器具間隔最大限            |                    | 2.5  | 71 | 65 | 60 | 56  | 68 | 63 | 58 | 54  | 63 | 58 | 55 | 51  | 58 | 54 | 51 | 48 | 43 |
|                | 横方向 (A)            | 縦方向 (B)            | 3.0  | 73 | 68 | 63 | 59  | 70 | 65 | 61 | 57  | 65 | 61 | 57 | 54  | 60 | 57 | 54 | 51 | 46 |
| H <sub>m</sub> | 1.09H <sub>m</sub> | 1.09H <sub>m</sub> | 4.0  | 76 | 71 | 67 | 64  | 73 | 69 | 65 | 62  | 67 | 64 | 61 | 58  | 62 | 60 | 57 | 55 | 49 |
|                |                    |                    | 5.0  | 77 | 74 | 70 | 67  | 75 | 71 | 68 | 65  | 69 | 66 | 64 | 61  | 64 | 62 | 60 | 58 | 52 |
|                |                    |                    | 7.0  | 79 | 76 | 74 | 71  | 77 | 74 | 71 | 69  | 71 | 69 | 67 | 65  | 66 | 64 | 63 | 61 | 55 |
|                |                    |                    | 10.0 | 81 | 79 | 77 | 75  | 78 | 76 | 74 | 72  | 73 | 71 | 70 | 68  | 68 | 67 | 65 | 64 | 58 |

