

屋内照明器具特性	
品番 (品名)	LSEW4001YF
光源	LDA4L-H-E17/S/4 ×1 440.0 lm
管理番号	K0160307(0)DR1
BZ分類	BZ9

器具効率	50%	反射率	天井	80%				70%				50%				30%				0%
			壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
上方光束	25%	床	10%				10%				10%				10%				0%	
下方光束	25%	室指数	照明率 (X0.01)																ZCM	
保守率	良 0.63	0.6	2.2	1.6	1.2	0.9	2.0	1.4	1.1	0.8	1.6	1.2	0.9	0.7	1.3	0.9	0.7	0.5	0.3	
	中 0.6	0.8	2.6	2.0	1.5	1.2	2.4	1.8	1.4	1.1	1.9	1.5	1.2	1.0	1.5	1.2	1.0	0.8	0.4	
	否 0.56	1.0	2.9	2.3	1.9	1.5	2.6	2.1	1.7	1.4	2.1	1.7	1.4	1.2	1.7	1.4	1.1	1.0	0.6	
		1.25	3.2	2.6	2.2	1.8	2.9	2.4	2.0	1.7	2.4	2.0	1.7	1.4	1.9	1.6	1.4	1.2	0.7	
下方投影面積	cm ²	1.5	3.4	2.8	2.4	2.1	3.1	2.6	2.2	1.9	2.5	2.2	1.9	1.6	2.0	1.7	1.5	1.3	0.8	
		2.0	3.6	3.2	2.8	2.5	3.3	2.9	2.6	2.3	2.8	2.4	2.2	1.9	2.2	2.0	1.8	1.6	1.0	
取付高さ	器具間隔最大限		2.5	3.8	3.4	3.1	2.8	3.5	3.1	2.8	2.6	2.9	2.6	2.4	2.2	2.4	2.1	2.0	1.8	1.2
	横方向 (A)	縦方向 (B)	3.0	4.0	3.6	3.3	3.0	3.6	3.3	3.0	2.8	3.0	2.8	2.6	2.4	2.5	2.3	2.1	1.9	1.3
H _m	1.65H _m	1.55H _m	4.0	4.1	3.8	3.6	3.3	3.8	3.5	3.3	3.1	3.2	3.0	2.8	2.6	2.6	2.4	2.3	2.2	1.5
			5.0	4.2	4.0	3.7	3.5	3.9	3.7	3.5	3.3	3.3	3.1	2.9	2.8	2.7	2.6	2.4	2.3	1.6
			7.0	4.4	4.2	4.0	3.8	4.1	3.9	3.7	3.5	3.4	3.3	3.1	3.0	2.8	2.7	2.6	2.5	1.8
			10.0	4.5	4.3	4.2	4.0	4.2	4.0	3.9	3.8	3.5	3.4	3.3	3.2	2.9	2.9	2.8	2.7	1.9

