

屋内照明器具特性

品番 (品名)	LGB87082Z														
光源	LDA4L-H-E17/S/4 x1 440.0lm														
管理番号	K0185908(0)DB1														
BZ分類	BZ5/1.8/BZ6														

器具効率	92%	天井	80%				70%				50%				30%				0%	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%	
		床	10%				10%				10%				10%				0%	
上方光束	30%																			
下方光束	62%																			
		室指数	照明率 (X0.01) ZCM																	
保守率	良 0.67 中 0.63 否 0.56	0.6	47	37	30	25	45	35	29	24	40	32	26	22	35	29	24	21	17	
		0.8	55	45	38	32	52	43	36	31	46	39	33	29	41	35	30	27	22	
		1.0	61	51	44	38	57	48	42	37	51	44	38	34	45	39	35	31	26	
		1.25	66	56	50	44	62	54	47	42	55	48	43	39	49	43	39	36	29	
下方投影面積	c m ²	1.5	69	61	54	49	65	58	52	47	58	52	47	43	51	46	42	39	32	
		2.0	74	67	61	56	70	63	58	53	62	57	53	49	55	51	47	44	37	
取付高さ	器具間隔最大限		2.5	77	71	65	61	73	67	62	58	65	60	56	53	58	54	51	48	40
	横方向 (A)	縦方向 (B)	3.0	79	74	69	64	75	70	66	62	67	63	59	56	60	56	53	51	42
H m	1.20H m	1.15H m	4.0	82	78	73	70	78	74	70	67	70	66	63	61	62	60	57	55	46
			5.0	84	80	76	73	80	76	73	70	72	69	66	64	64	62	59	58	48
			7.0	86	83	80	78	82	79	77	74	74	72	69	67	66	64	63	61	51
			10.0	88	86	84	81	84	82	80	78	76	74	72	71	68	66	65	64	54

