

屋内照明器具特性	
品番(品名)	LGB19325WF
光源	LDA7L-D-G/S/Z6 ×3      810.0 lm
管理番号	K0189055(1)DR1
BZ分類	BZ10/8.5/BZ9

器具効率	82%	天井	80%				70%				50%				30%				0%	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%	
上方光束	39%	床	10%				10%				10%				10%				0%	
下方光束	43%	室指数	照明率 (X0.01)																ZCM	
保守率	良	0.63	0.6	3.5	2.5	1.8	1.3	3.2	2.3	1.6	1.2	2.6	1.9	1.4	1.0	2.1	1.5	1.1	8	3
	中	0.6	0.8	4.2	3.2	2.4	1.9	3.8	2.9	2.2	1.8	3.1	2.4	1.9	1.5	2.5	1.9	1.5	12	6
	否	0.56	1.0	4.7	3.7	2.9	2.4	4.3	3.4	2.7	2.2	3.5	2.8	2.3	1.8	2.8	2.2	1.8	15	8
			1.25	5.2	4.2	3.5	2.9	4.7	3.8	3.2	2.7	3.9	3.2	2.7	2.2	3.1	2.6	2.2	18	11
下方投影面積		cm <sup>2</sup>	1.5	5.5	4.6	3.9	3.3	5.0	4.2	3.6	3.1	4.1	3.5	3.0	2.6	3.3	2.9	2.4	2.1	13
等価発光面積		cm <sup>2</sup>	2.0	6.0	5.2	4.5	4.0	5.5	4.8	4.2	3.7	4.5	4.0	3.5	3.1	3.7	3.3	2.9	2.6	17
取付高さ	器具間隔最大限		2.5	6.3	5.6	5.0	4.5	5.8	5.1	4.6	4.1	4.8	4.3	3.9	3.5	3.9	3.5	3.2	2.9	1.9
	横方向(A)	縦方向(B)	3.0	6.5	5.9	5.3	4.8	6.0	5.4	4.9	4.5	5.0	4.6	4.2	3.8	4.1	3.8	3.5	3.2	2.1
Hm	2.60Hm	2.60Hm	4.0	6.8	6.3	5.8	5.4	6.3	5.8	5.4	5.0	5.3	4.9	4.6	4.3	4.4	4.1	3.8	3.6	2.5
			5.0	7.0	6.5	6.1	5.7	6.5	6.1	5.7	5.4	5.5	5.2	4.9	4.6	4.6	4.3	4.1	3.8	2.7
			7.0	7.2	6.9	6.5	6.2	6.7	6.4	6.1	5.8	5.7	5.5	5.2	5.0	4.8	4.6	4.4	4.2	3.0
			10.0	7.4	7.2	6.9	6.6	6.9	6.7	6.4	6.2	5.9	5.7	5.5	5.3	5.0	4.8	4.7	4.5	3.3

