

屋内照明器具特性

品番 (品名)	L G W C 8 5 2 1 8 F				
光源	LDA4L-H-E17/S/4 x1 440.0 lm				
管理番号	K0168589(0)DB1				
BZ分類	BZ7/0.7/BZ8/4.5/BZ7				

器具効率	54%	天井	80%				70%				50%				30%				0%		
	上方光束		13%	反射率	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
	下方光束		41%		床	10%				10%				10%				10%			
室指数	照明率 (X0.01)																			ZCM	
保守率	良	0.63	0.6	2.6	1.9	1.5	1.2	2.5	1.8	1.4	1.1	2.2	1.7	1.3	1.0	2.0	1.5	1.2	1.0	8	
	中	0.6	0.8	3.0	2.3	1.8	1.5	2.8	2.2	1.7	1.4	2.5	2.0	1.6	1.3	2.2	1.8	1.4	1.2	9	
	否	0.56	1.0	3.3	2.6	2.1	1.7	3.1	2.5	2.0	1.7	2.8	2.2	1.8	1.5	2.4	2.0	1.7	1.4	11	
	下方投影面積	c m ²		1.25	3.6	2.9	2.4	2.0	3.4	2.8	2.3	2.0	3.0	2.5	2.1	1.8	2.6	2.2	1.9	1.6	13
等価発光面積	c m ²		1.5	3.8	3.2	2.7	2.3	3.6	3.0	2.6	2.2	3.2	2.7	2.4	2.0	2.8	2.4	2.1	1.9	15	
	c m ²		2.0	4.1	3.6	3.1	2.8	3.9	3.4	3.0	2.7	3.5	3.1	2.7	2.4	3.1	2.8	2.5	2.2	18	
取付高さ	器具間隔最大限		2.5	4.4	3.9	3.5	3.1	4.1	3.7	3.3	3.0	3.7	3.3	3.0	2.7	3.3	3.0	2.8	2.5	21	
	横方向 (A)	縦方向 (B)	3.0	4.5	4.1	3.7	3.4	4.3	3.9	3.6	3.2	3.9	3.5	3.2	3.0	3.5	3.2	3.0	2.7	23	
Hm	0.65Hm	0.66Hm	4.0	4.7	4.4	4.1	3.8	4.5	4.2	3.9	3.6	4.1	3.8	3.6	3.3	3.7	3.5	3.3	3.1	26	
			5.0	4.9	4.6	4.3	4.0	4.7	4.4	4.1	3.9	4.2	4.0	3.8	3.6	3.8	3.6	3.5	3.3	28	
			7.0	5.1	4.8	4.6	4.4	4.8	4.6	4.4	4.2	4.4	4.2	4.1	3.9	4.0	3.9	3.7	3.6	31	
			10.0	5.2	5.0	4.8	4.7	5.0	4.8	4.7	4.5	4.6	4.4	4.3	4.2	4.2	4.0	3.9	3.8	33	

