

屋内照明器具特性

品番 (品名)	XLGEJ 552HF																
光源	LDA4L-H-E17/S/4 x1 440.0lm																
管理番号	K0188857(0)DB1																
BZ分類	BZ10																

器具効率	49%	天井	80%				70%				50%				30%				0%	
			壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
上方光束	30%	反射率	10%				10%				10%				10%				0%	
下方光束	19%		床	10%				10%				10%				10%				0%
室指数			照明率 (X0.01) ZCM																	
保守率	良	0.63	0.6	2.0	1.4	1.0	0.8	1.8	1.3	0.9	0.7	1.4	1.0	0.7	0.5	1.0	0.7	0.5	0.3	0
	中	0.6	0.8	2.4	1.8	1.4	1.1	2.1	1.6	1.2	1.0	1.6	1.2	0.9	0.7	1.2	0.9	0.7	0.5	1
	否	0.56	1.0	2.7	2.1	1.7	1.3	2.4	1.9	1.5	1.2	1.8	1.4	1.2	0.9	1.3	1.1	0.8	0.6	2
			1.25	2.9	2.4	1.9	1.6	2.6	2.1	1.7	1.5	2.0	1.7	1.4	1.1	1.5	1.2	1.0	0.8	3
下方投影面積		cm ²	1.5	3.1	2.6	2.2	1.9	2.8	2.3	2.0	1.7	2.2	1.8	1.5	1.3	1.6	1.3	1.1	0.9	4
等価発光面積		cm ²	2.0	3.4	2.9	2.5	2.2	3.0	2.6	2.3	2.0	2.4	2.1	1.8	1.6	1.8	1.5	1.3	1.2	5
取付高さ	器具間隔最大限		2.5	3.6	3.2	2.8	2.5	3.2	2.8	2.5	2.3	2.5	2.2	2.0	1.8	1.9	1.7	1.5	1.3	6
	横方向 (A)	縦方向 (B)	3.0	3.7	3.3	3.0	2.7	3.3	3.0	2.7	2.5	2.6	2.4	2.2	2.0	2.0	1.8	1.6	1.5	7
Hm	0.00Hm	0.00Hm	4.0	3.9	3.6	3.3	3.0	3.5	3.2	3.0	2.7	2.8	2.6	2.4	2.2	2.1	2.0	1.8	1.7	9
			5.0	4.0	3.7	3.5	3.2	3.6	3.4	3.1	2.9	2.9	2.7	2.5	2.4	2.2	2.1	1.9	1.8	10
			7.0	4.1	3.9	3.7	3.5	3.7	3.6	3.4	3.2	3.0	2.9	2.7	2.6	2.3	2.2	2.1	2.0	1.1
			10.0	4.2	4.1	3.9	3.8	3.9	3.7	3.6	3.4	3.1	3.0	2.9	2.8	2.4	2.3	2.3	2.2	1.3

