

屋内照明器具特性

品番 (品名)	XLGB1853	
光源	LLD2000VCE1 ×1	531.0 lm
管理番号	K0189911(2)DR1	
BZ分類	BZ4/0.7/BZ3/1.1/BZ4	

器具効率	76%	天井	80%				70%				50%				30%				0%		
	上方光束 2%		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%	
下方光束	74%	床		10%				10%				10%				10%				0%	
室指数	照明率 (X0.01)																				ZCM
保守率	良	0.67	0.6	4.6	3.8	3.2	2.9	4.5	3.7	3.2	2.9	4.3	3.6	3.2	2.8	4.2	3.6	3.1	2.8	2.7	
	中	0.63	0.8	5.4	4.6	4.1	3.7	5.3	4.5	4.0	3.7	5.1	4.4	4.0	3.6	4.9	4.3	3.9	3.6	3.4	
	否	0.56	1.0	5.9	5.1	4.6	4.2	5.7	5.1	4.6	4.2	5.5	4.9	4.5	4.2	5.3	4.8	4.4	4.1	3.9	
			1.25	6.3	5.6	5.1	4.7	6.1	5.5	5.1	4.7	5.9	5.4	5.0	4.7	5.7	5.2	4.9	4.6	4.4	
下方投影面積	cm ²		1.5	6.6	6.0	5.5	5.1	6.4	5.9	5.4	5.1	6.2	5.7	5.3	5.0	5.9	5.5	5.2	4.9	4.7	
等価発光面積	cm ²		2.0	6.9	6.4	6.0	5.7	6.8	6.3	6.0	5.6	6.5	6.2	5.8	5.5	6.3	6.0	5.7	5.5	5.2	
取付高さ	器具間隔最大限		2.5	7.2	6.7	6.4	6.1	7.0	6.6	6.3	6.0	6.8	6.4	6.2	5.9	6.5	6.3	6.0	5.8	5.6	
	横方向 (A)	縦方向 (B)	3.0	7.3	6.9	6.6	6.3	7.2	6.8	6.5	6.3	6.9	6.6	6.4	6.2	6.7	6.5	6.2	6.0	5.8	
Hm	1.24Hm	1.24Hm	4.0	7.5	7.2	7.0	6.7	7.4	7.1	6.9	6.7	7.1	6.9	6.7	6.5	6.9	6.7	6.5	6.4	6.1	
			5.0	7.7	7.4	7.2	7.0	7.5	7.3	7.1	6.9	7.3	7.1	6.9	6.7	7.0	6.9	6.7	6.6	6.3	
			7.0	7.8	7.6	7.4	7.3	7.7	7.5	7.3	7.2	7.4	7.3	7.2	7.0	7.2	7.1	7.0	6.9	6.6	
			10.0	7.9	7.8	7.6	7.5	7.8	7.7	7.5	7.4	7.6	7.4	7.3	7.2	7.3	7.2	7.1	7.0	6.8	

