

# 屋内照明器具特性

|         |                  |          |
|---------|------------------|----------|
| 品番 (品名) | XLGB1854         |          |
| 光源      | LLD2000LCE1 ×1   | 531.0 lm |
| 管理番号    | K0189912 (2) DR1 |          |
| BZ分類    | BZ4/8.5/BZ5      |          |

|        |                 |         |      |     |    |    |     |     |    |    |     |     |    |    |     |     |    |    |    |     |
|--------|-----------------|---------|------|-----|----|----|-----|-----|----|----|-----|-----|----|----|-----|-----|----|----|----|-----|
| 器具効率   | 79%             | 天井      | 80%  |     |    |    | 70% |     |    |    | 50% |     |    |    | 30% |     |    |    | 0% |     |
|        | 上方光束<br>3%      |         | 反射率  | 70  | 50 | 30 | 10  | 70  | 50 | 30 | 10  | 70  | 50 | 30 | 10  | 70  | 50 | 30 | 10 | 0%  |
| 下方光束   | 76%             | 床       |      | 10% |    |    |     | 10% |    |    |     | 10% |    |    |     | 10% |    |    |    | 0%  |
| 室指数    | 照明率 ( X0.01 )   |         |      |     |    |    |     |     |    |    |     |     |    |    |     |     |    |    |    | ZCM |
| 保守率    | 良               | 0.67    | 0.6  | 48  | 39 | 33 | 29  | 46  | 38 | 33 | 29  | 44  | 37 | 32 | 29  | 43  | 36 | 32 | 28 | 27  |
|        | 中               | 0.63    | 0.8  | 55  | 47 | 41 | 37  | 54  | 46 | 41 | 37  | 52  | 45 | 40 | 37  | 50  | 44 | 40 | 36 | 34  |
|        | 否               | 0.56    | 1.0  | 60  | 53 | 47 | 43  | 59  | 52 | 47 | 43  | 56  | 50 | 46 | 42  | 54  | 49 | 45 | 42 | 40  |
|        |                 |         | 1.25 | 65  | 58 | 52 | 48  | 63  | 57 | 52 | 48  | 61  | 55 | 51 | 47  | 58  | 53 | 50 | 47 | 45  |
| 下方投影面積 | cm <sup>2</sup> |         | 1.5  | 67  | 61 | 56 | 52  | 66  | 60 | 56 | 52  | 63  | 58 | 54 | 51  | 61  | 57 | 53 | 50 | 48  |
| 等価発光面積 | cm <sup>2</sup> |         | 2.0  | 71  | 66 | 62 | 58  | 70  | 65 | 61 | 58  | 67  | 63 | 60 | 57  | 65  | 61 | 58 | 56 | 53  |
| 取付高さ   | 器具間隔最大限         |         | 2.5  | 74  | 69 | 65 | 62  | 72  | 68 | 65 | 62  | 70  | 66 | 63 | 60  | 67  | 64 | 62 | 59 | 57  |
|        | 横方向 (A)         | 縦方向 (B) | 3.0  | 76  | 72 | 68 | 65  | 74  | 70 | 67 | 65  | 71  | 68 | 66 | 63  | 69  | 66 | 64 | 62 | 59  |
| Hm     | 1.25Hm          | 1.25Hm  | 4.0  | 78  | 75 | 72 | 69  | 76  | 73 | 71 | 68  | 74  | 71 | 69 | 67  | 71  | 69 | 67 | 66 | 63  |
|        |                 |         | 5.0  | 79  | 76 | 74 | 72  | 78  | 75 | 73 | 71  | 75  | 73 | 71 | 69  | 73  | 71 | 69 | 68 | 65  |
|        |                 |         | 7.0  | 81  | 79 | 77 | 75  | 79  | 77 | 76 | 74  | 77  | 75 | 74 | 72  | 74  | 73 | 72 | 71 | 68  |
|        |                 |         | 10.0 | 82  | 80 | 79 | 78  | 81  | 79 | 78 | 77  | 78  | 77 | 76 | 75  | 76  | 75 | 74 | 73 | 70  |

