

屋内照明器具特性	
品番 (品名)	XLGB1855
光源	LLD2000VCE1 ×1 531.0 lm
管理番号	K0189912 (2) DR1
BZ分類	BZ4/8.5/BZ5

器具効率		79 %	反射率	天井	80 %				70 %				50 %				30 %				0 %	
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %	
				床	10 %				10 %				10 %				10 %				0 %	
				室指数	照明率 ( X0.01 )																ZCM	
保守率		良 中 否	0.67	0.6	48	39	33	29	46	38	33	29	44	37	32	29	43	36	32	28	27	
			0.63	0.8	55	47	41	37	54	46	41	37	52	45	40	37	50	44	40	36	34	
			0.56	1.0	60	53	47	43	59	52	47	43	56	50	46	42	54	49	45	42	40	
				1.25	65	58	52	48	63	57	52	48	61	55	51	47	58	53	50	47	45	
下方投影面積		cm <sup>2</sup>		1.5	67	61	56	52	66	60	56	52	63	58	54	51	61	57	53	50	48	
等価発光面積			cm <sup>2</sup>	2.0	71	66	62	58	70	65	61	58	67	63	60	57	65	61	58	56	53	
取付高さ	器具間隔最大限			2.5	74	69	65	62	72	68	65	62	70	66	63	60	67	64	62	59	57	
	横方向 ( A )			縦方向 ( B )	3.0	76	72	68	65	74	70	67	65	71	68	66	63	69	66	64	62	59
H m	1.25 H m	1.25 H m		4.0	78	75	72	69	76	73	71	68	74	71	69	67	71	69	67	66	63	
			5.0	79	76	74	72	78	75	73	71	75	73	71	69	73	71	69	68	65		
			7.0	81	79	77	75	79	77	76	74	77	75	74	72	74	73	72	71	68		
			10.0	82	80	79	78	81	79	78	77	78	77	76	75	76	75	74	73	70		

