

屋内照明器具特性

品番 (品名)	XLGB1856														
光源	LLD2000CU1 x1 566.0 lm														
管理番号	K0189918(0)DR1														
BZ分類	BZ4/3.5/BZ5														

器具効率	88%	天井	80%				70%				50%				30%				0%	
			壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
上方光束	4%	反射率	床	10%				10%				10%				10%				0%
下方光束	84%		室指数	照明率 (X0.01) ZCM																
保守率	良 中 否	0.67	0.6	5.2	4.1	3.5	3.0	5.0	4.1	3.5	3.0	4.8	4.0	3.4	3.0	4.6	3.8	3.3	2.9	2.8
		0.63	0.8	6.0	5.1	4.4	3.9	5.9	5.0	4.4	3.9	5.6	4.8	4.3	3.9	5.4	4.7	4.2	3.8	3.6
		0.56	1.0	6.6	5.7	5.1	4.6	6.4	5.6	5.0	4.6	6.1	5.4	4.9	4.5	5.9	5.3	4.8	4.4	4.2
			1.25	7.1	6.3	5.7	5.2	6.9	6.2	5.6	5.2	6.6	6.0	5.5	5.1	6.3	5.8	5.4	5.0	4.8
下方投影面積	c m ²	1.5	7.4	6.7	6.1	5.7	7.3	6.6	6.0	5.6	6.9	6.4	5.9	5.5	6.6	6.1	5.8	5.4	5.2	
		2.0	7.9	7.3	6.8	6.3	7.7	7.1	6.7	6.3	7.4	6.9	6.5	6.1	7.1	6.7	6.3	6.0	5.7	
取付高さ	器具間隔最大限		2.5	8.2	7.6	7.2	6.8	8.0	7.5	7.1	6.7	7.7	7.2	6.9	6.6	7.3	7.0	6.7	6.4	6.1
	横方向 (A)	縦方向 (B)	3.0	8.4	7.9	7.5	7.1	8.2	7.8	7.4	7.1	7.9	7.5	7.2	6.9	7.6	7.3	7.0	6.7	6.4
H m	1.26 H m	1.26 H m	4.0	8.6	8.2	7.9	7.6	8.4	8.1	7.8	7.5	8.1	7.8	7.6	7.3	7.8	7.6	7.4	7.2	6.8
			5.0	8.8	8.5	8.2	7.9	8.6	8.3	8.1	7.8	8.3	8.0	7.8	7.6	8.0	7.8	7.6	7.4	7.1
			7.0	9.0	8.7	8.5	8.3	8.8	8.6	8.4	8.2	8.5	8.3	8.1	8.0	8.2	8.0	7.9	7.7	7.4
			10.0	9.1	8.9	8.8	8.6	8.9	8.8	8.6	8.5	8.6	8.5	8.4	8.2	8.3	8.2	8.1	8.0	7.6

