

屋内照明器具特性	
品番 (品名)	FYY44045 (JYOUJI)
光源	LDL40S.N/29/38-K ×1 3800.0 lm
管理番号	K0171212 (1) DB1
BZ分類	BZ7

器具効率	100%	天井	80%				70%				50%				30%				0%	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%	
上方光束	26%	床	10%				10%				10%				10%				0%	
下方光束	74%	室指数	照明率 (×0.01) ZCM																	
保守率	良 中 否 0.81 0.77 0.68	0.6	48	35	26	20	45	33	25	20	40	30	23	18	35	27	21	17	13	
		0.8	56	44	35	29	53	42	33	27	47	38	31	25	42	34	28	23	19	
		1.0	63	50	41	35	59	48	40	33	52	43	36	31	46	39	33	28	23	
		1.25	68	57	48	41	65	54	46	40	57	49	42	37	51	44	38	34	28	
下方投影面積	c m <sup>2</sup>	1.5	72	62	53	47	69	59	51	45	61	53	47	41	54	48	43	38	32	
		2.0	78	69	61	55	74	66	59	53	67	60	54	49	59	54	49	45	37	
取付高さ	器具間隔最大限		2.5	82	74	67	61	78	70	64	59	70	64	59	54	63	58	53	42	
	横方向 (A)	縦方向 (B)	3.0	85	77	71	65	81	74	68	63	73	67	62	58	65	61	57	45	
1.5m	2.74m	2.17m	4.0	89	82	77	72	84	79	74	69	76	72	68	64	69	65	62	59	50
2	3.6	2.74	5.0	91	86	81	76	87	82	77	73	79	75	71	68	71	68	65	62	53
2.5	4.46	3.33	7.0	94	90	86	82	90	86	82	79	82	78	76	73	74	71	69	67	58
3	5.32	3.94	10.0	96	93	90	87	92	89	86	84	84	82	79	77	76	74	73	71	61

