

<b>屋内照明器具特性</b>	
品番 (品名)	<b>XLGB1869</b>
光源	LLD2000LCE1 ×1                      531.0 lm
管理番号	K0190090 (1) DR1
BZ分類	BZ3/0.7/BZ2/1.8/BZ3

器具効率	70%	天井	80%				70%				50%				30%				0%	
	上方光束 1%		反射率	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
下方光束	69%	床		10%				10%				10%				10%				0%
		室指数	照明率 ( X0.01)																ZCM	
保守率	良	0.67	0.6	45	38	34	30	45	38	33	30	43	37	33	30	42	36	33	30	29
	中	0.63	0.8	52	46	41	38	51	45	41	38	50	45	41	38	48	44	40	38	37
	否	0.56	1.0	57	51	47	44	56	50	46	43	54	49	46	43	52	48	45	43	41
			1.25	60	55	51	48	59	54	51	48	57	53	50	48	56	52	50	47	46
下方投影面積		cm <sup>2</sup>	1.5	63	58	54	51	62	57	54	51	60	56	53	51	58	55	52	50	49
等価発光面積		cm <sup>2</sup>	2.0	66	62	59	56	65	61	58	56	63	60	57	55	61	59	56	55	53
取付高さ	器具間隔最大限		2.5	68	64	62	59	67	64	61	59	65	62	60	58	63	61	59	57	56
	横方向 (A)	縦方向 (B)	3.0	69	66	64	62	68	65	63	61	66	64	62	60	64	62	61	59	58
Hm	1.31Hm	1.31Hm	4.0	70	68	66	65	69	67	66	64	68	66	64	63	66	65	63	62	60
			5.0	71	70	68	66	70	69	67	66	69	67	66	65	67	66	65	64	62
			7.0	72	71	70	69	72	70	69	68	70	69	68	67	68	67	66	66	64
			10.0	73	72	71	71	72	72	71	70	71	70	69	69	69	68	68	67	65

