

屋内照明器具特性

品番 (品名)	LSEB4104Z															
光源	LDA4L-H-E17/S/4 x1 440.0lm															
管理番号	K0187162(0)DR1															
BZ分類	BZ6															

器具効率	95%	天井	80%				70%				50%				30%				0%		
			反射率	壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
				床	10%				10%				10%				10%				0%
上方光束 下方光束	36% 59%	室指数	照明率 (X0.01) ZCM																		
保守率	良 中 否 0.67 0.63 0.56	0.6	47	36	29	24	44	34	27	22	38	30	24	20	33	26	22	18	14		
		0.8	55	44	37	31	52	42	35	30	45	37	31	27	39	32	28	24	19		
		1.0	61	50	43	37	57	48	41	36	49	42	36	32	43	37	32	29	23		
		1.25	66	56	49	43	62	53	47	41	54	47	42	37	46	41	37	33	26		
下方投影面積 等価発光面積	c m ² c m ²	1.5	70	61	54	48	65	57	51	46	57	50	45	41	49	44	40	37	29		
		2.0	75	67	61	55	70	63	57	53	61	56	51	47	53	49	45	42	33		
取付 高さ	器具間隔最大限		2.5	78	71	66	61	73	67	62	58	64	59	55	52	56	52	49	46	36	
	横方向 (A) H m	縦方向 (B) H m	3.0	80	74	69	65	76	70	65	61	66	62	58	55	57	54	51	49	39	
			4.0	83	78	74	70	78	74	70	66	69	66	62	59	60	57	55	53	42	
			5.0	85	81	77	74	80	77	73	70	71	68	65	63	62	59	57	55	44	
			7.0	88	84	81	79	83	80	77	74	73	71	69	66	64	62	60	59	47	
			10.0	90	87	85	82	85	82	80	78	75	73	71	70	66	64	63	62	50	

