

屋内照明器具特性	
品番 (品名)	FYY46000
光源	LDL40S.N/29/38K(3800) ×1 3800.0 1m
管理番号	K0124842(0)DB1
BZ分類	BZ10/0.7/BZ9

器具効率	58%	天井	80%				70%				50%				30%				0%	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%	
上方光束	54%	床	10%				10%				10%				10%				0%	
下方光束	4%	室指数	照明率 (X0.01)																ZCM	
保守率	良	0.81	0.6	2.5	1.9	1.5	1.2	2.1	1.6	1.3	1.1	1.5	1.1	9	7	9	7	6	5	0
	中	0.77	0.8	2.9	2.3	1.9	1.6	2.5	2.0	1.7	1.4	1.8	1.4	1.2	1.0	1.1	9	7	6	0
	否	0.68	1.0	3.3	2.7	2.3	2.0	2.8	2.3	2.0	1.8	2.0	1.7	1.4	1.3	1.2	1.0	9	8	0
			1.25	3.6	3.1	2.7	2.4	3.1	2.6	2.3	2.1	2.1	1.9	1.7	1.5	1.3	1.1	1.0	9	1
下方投影面積		cm ²	1.5	3.8	3.3	2.9	2.7	3.3	2.9	2.6	2.3	2.3	2.0	1.8	1.7	1.4	1.2	1.1	1.0	1
等価発光面積		cm ²	2.0	4.1	3.7	3.4	3.1	3.5	3.2	2.9	2.7	2.5	2.3	2.1	1.9	1.5	1.4	1.3	1.2	1
取付高さ	器具間隔最大限		2.5	4.3	3.9	3.6	3.4	3.7	3.4	3.2	3.0	2.6	2.4	2.3	2.1	1.6	1.5	1.4	1.3	1
	横方向 (A)	縦方向 (B)	3.0	4.4	4.1	3.8	3.6	3.8	3.6	3.3	3.1	2.7	2.5	2.4	2.3	1.6	1.6	1.5	1.4	2
1.5m	0	2	4.0	4.5	4.3	4.1	3.9	3.9	3.7	3.6	3.4	2.8	2.7	2.6	2.5	1.7	1.7	1.6	1.5	2
2	0	2.57	5.0	4.6	4.4	4.3	4.1	4.0	3.9	3.7	3.6	2.9	2.8	2.7	2.6	1.8	1.7	1.7	1.6	2
2.5	0	3.12	7.0	4.8	4.6	4.5	4.3	4.2	4.0	3.9	3.8	3.0	2.9	2.8	2.7	1.8	1.8	1.8	1.7	2
3	0	3.68	10.0	4.9	4.8	4.6	4.5	4.2	4.1	4.1	4.0	3.0	3.0	2.9	2.9	1.9	1.9	1.8	1.8	2

