

屋内照明器具特性

品番 (品名)	FYY46010															
光源	LDL40S.N/14/26(2600A) ×1 2600.0 1m															
管理番号	K0124841(2)DB1															
BZ分類	BZ5/3.5/BZ6															

器具効率	79%	天井	80%				70%				50%				30%				0%	
			壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
上方光束	37%	室指数	床	10%				10%				10%				10%				0%
下方光束	42%		照明率 (X0.01) ZCM																	
保守率	良 中 否	0.81	0.6	3.9	3.0	2.4	2.0	3.6	2.8	2.3	1.9	3.1	2.4	2.0	1.7	2.6	2.1	1.7	1.5	1.1
		0.77	0.8	4.6	3.7	3.1	2.7	4.2	3.5	2.9	2.5	3.6	3.0	2.6	2.2	3.0	2.6	2.2	2.0	1.5
			1.0	5.1	4.2	3.6	3.2	4.7	4.0	3.4	3.0	4.0	3.4	3.0	2.7	3.3	2.9	2.6	2.3	1.7
		0.68	1.25	5.5	4.7	4.2	3.7	5.1	4.4	3.9	3.5	4.3	3.8	3.4	3.1	3.6	3.2	2.9	2.7	2.0
下方投影面積			cm ²																	
等価発光面積			cm ²																	
取付高さ	器具間隔最大限		2.5	6.5	6.0	5.5	5.1	6.0	5.6	5.2	4.8	5.1	4.8	4.5	4.2	4.3	4.1	3.8	3.6	2.7
	横方向 (A)	縦方向 (B)	3.0	6.7	6.2	5.8	5.5	6.2	5.8	5.4	5.1	5.3	5.0	4.7	4.5	4.5	4.2	4.0	3.9	2.9
1.5m	2.08m	2.19m	4.0	6.9	6.5	6.2	5.9	6.4	6.1	5.8	5.5	5.5	5.3	5.0	4.8	4.7	4.5	4.3	4.2	3.1
2	2.74	2.78	5.0	7.1	6.7	6.5	6.2	6.6	6.3	6.0	5.8	5.7	5.4	5.3	5.1	4.8	4.6	4.5	4.4	3.3
2.5	3.41	3.39	7.0	7.2	7.0	6.8	6.6	6.7	6.5	6.3	6.2	5.8	5.7	5.5	5.4	4.9	4.8	4.7	4.6	3.5
3	4.07	4.01	10.0	7.4	7.2	7.0	6.9	6.9	6.7	6.6	6.4	5.9	5.8	5.7	5.6	5.1	5.0	4.9	4.8	3.6

