

屋内照明器具特性

品番 (品名)	LGB10778	
光源	LED6200_70_1125 ×1	1125.0 lm
管理番号	K0157912(0)DB1	
BZ分類	BZ4/6.0/BZ5	

器具効率	100%	天井	80%				70%				50%				30%				0%				
	上方光束 8%		下方光束 92%	反射率	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%		
				壁	10%				10%				10%				10%				0%		
室指数	照明率 (X0.01)																				ZCM		
保守率	良	0.63	0.6	0.6	0.56	0.6	59	48	41	36	57	47	40	35	54	45	39	35	52	44	38	34	32
	中	0.6	0.6	0.6	0.6	0.8	69	58	51	46	67	57	50	45	63	55	49	45	60	53	48	44	41
	否	0.56	0.56	0.56	0.56	1.0	75	65	58	53	73	64	57	52	69	62	56	51	66	59	54	50	47
						1.25	81	72	65	60	78	70	64	59	74	68	62	58	71	65	61	57	54
下方投影面積	c m ²		c m ²		1.5	84	76	70	65	82	75	69	64	78	72	67	63	74	69	65	61	58	
	等価発光面積		c m ²		2.0	89	83	77	73	87	81	76	72	83	78	73	70	79	75	71	68	64	
取付高さ	器具間隔最大限				2.5	92	87	82	78	90	85	80	77	86	82	78	74	82	78	75	72	68	
	横方向 (A)	縦方向 (B)			3.0	95	90	85	81	92	88	84	80	88	84	81	78	84	81	78	76	71	
1.5m	2.13m	1.49m			4.0	97	93	90	86	95	91	88	85	91	88	85	83	87	84	82	80	76	
2	2.83	1.67			5.0	99	96	93	90	97	94	91	88	93	90	88	86	89	87	85	83	78	
2.5	3.53	2.48			7.0	101	99	96	94	99	97	94	92	95	93	91	89	91	89	88	86	82	
3	4.24	2.8			10.0	103	101	99	97	100	99	97	96	96	95	94	92	92	91	90	89	84	

