

屋内照明器具特性

品番 (品名)	LGB10733K									
光源	LED6200_70_545 x1					545.0 lm				
管理番号	K0153705(0)DB1									
BZ分類	BZ5/0.7/BZ6/1.8/BZ7/4.5/BZ6									

器具効率	100%	天井	80%				70%				50%				30%				0%	
			壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
上方光束	7%	反射率	床	10%				10%				10%				10%				0%
下方光束	93%		室指数	照明率 (X0.01)																ZCM
保守率	良	0.67	0.6	55	43	35	29	53	42	34	29	50	40	33	28	47	38	32	28	25
	中	0.63	0.8	62	50	41	35	60	48	40	35	56	46	39	34	53	44	38	33	30
	否	0.56	1.0	67	55	46	39	65	53	45	39	60	51	43	38	56	48	42	37	33
			1.25	72	60	51	44	69	58	50	43	65	55	48	42	60	53	46	41	37
下方投影面積			1.5	76	64	56	49	73	63	55	48	68	59	52	47	64	56	50	45	41
等価発光面積			2.0	81	71	63	57	79	70	62	56	74	66	59	54	69	63	57	52	48
取付高さ	器具間隔最大限		2.5	85	76	69	63	83	74	68	62	78	71	65	60	73	67	62	58	53
	横方向 (A)	縦方向 (B)	3.0	88	80	74	68	86	78	72	66	81	75	69	64	76	71	66	62	58
Hm	1.25Hm	1.25Hm	4.0	92	86	80	75	90	84	78	74	85	80	75	71	80	76	72	69	64
			5.0	95	89	84	80	92	87	83	78	88	83	79	76	83	80	76	73	68
			7.0	98	94	90	86	96	92	88	85	91	88	85	82	87	84	81	79	74
			10.0	100	97	94	91	98	95	92	90	94	91	89	87	90	87	85	84	79

