

屋内照明器具特性

品番 (品名)	LGB11096									
光源	LED2700_70_300 x1					300.0 l m				
管理番号	K0148374 (0) DB 1									
BZ分類	BZ4/6.0/BZ3									

器具効率	100%	天井	80%				70%				50%				30%				0%		
	上方光束		0%	反射率	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
	下方光束		100%		床	10%				10%				10%				10%			
室指数	照明率 (X0.01)																			ZCM	
保守率	良	0.67	0.6	59	47	40	34	58	47	39	34	55	46	39	34	53	45	39	34	32	
	中	0.63	0.8	69	59	51	46	68	58	51	46	65	57	50	45	63	55	50	45	43	
	否	0.56	1.0	76	66	59	54	75	66	59	54	72	64	58	53	69	63	57	53	51	
			1.25	82	74	67	62	81	73	66	61	78	71	65	61	75	69	64	61	58	
下方投影面積			1.5	86	79	72	67	85	78	72	67	82	76	71	67	79	74	70	66	64	
	等価発光面積		2.0	92	86	80	76	90	85	80	75	88	83	78	75	85	81	77	74	72	
取付高さ	器具間隔最大限		2.5	95	90	85	81	94	89	85	81	91	87	83	80	88	85	82	79	77	
	横方向 (A)	縦方向 (B)	3.0	98	93	89	85	96	92	88	85	93	90	87	84	91	88	85	83	80	
Hm	1.24Hm	1.24Hm	4.0	100	97	93	91	99	96	93	90	96	93	91	89	94	91	89	87	85	
			5.0	102	99	96	94	101	98	95	93	98	96	94	92	96	94	92	90	88	
			7.0	104	102	100	98	103	101	99	97	100	98	97	95	98	96	95	94	91	
			10.0	105	104	102	101	104	103	101	100	102	100	99	98	99	98	97	96	94	

