

屋内照明器具特性	
品番 (品名)	LGB12602
光源	LGB12602 ×1 3610.0 l m
管理番号	K0127848 (0) DB 1
BZ分類	BZ5 / 1.4 / BZ4

器具効率	100 %	天井	80 %				70 %				50 %				30 %				0 %	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %	
上方光束	3 %	床	10 %				10 %				10 %				10 %				0 %	
下方光束	97 %	室指数	照明率 (X0.01)																ZCM	
保守率	良 0.67 中 0.63 否 0.56	0.6	56	44	36	31	55	43	36	31	52	42	35	30	50	41	35	30	28	
		0.8	67	55	47	42	65	54	47	41	62	53	46	41	59	51	45	41	38	
		1.0	73	63	55	50	72	62	55	49	68	60	54	49	65	58	52	48	46	
		1.25	80	70	63	57	78	69	62	57	74	67	61	56	71	65	60	55	53	
下方投影面積	c m ²	1.5	84	75	69	63	82	74	68	63	78	72	66	62	75	70	65	61	58	
		2.0	89	82	77	72	88	81	76	71	84	79	74	70	81	76	72	69	66	
取付高さ	器具間隔最大限		2.5	93	87	82	78	91	86	81	77	88	83	79	76	85	81	77	74	71
	横方向 (A)	縦方向 (B)	3.0	95	90	86	82	94	89	85	81	90	86	83	80	87	84	81	78	75
1.5m	2 m	2.01 m	4.0	98	94	91	87	97	93	90	87	93	90	87	85	90	88	85	83	80
2	2.63	2.63	5.0	100	97	94	91	99	95	93	90	95	93	90	88	92	90	88	86	83
2.5	3.27	3.28	7.0	102	100	97	95	101	98	96	94	97	96	94	92	94	93	91	90	86
3	3.92	3.93	10.0	104	102	100	99	102	101	99	98	99	98	96	95	96	95	94	93	89

