

屋内照明器具特性	
品番 (品名)	LGB15018Z
光源	LDA4L-H-E17/E/S/W/2 ×1 440.0 1 m
管理番号	K0123321(0)DB1
BZ分類	BZ4/1.1/BZ3

器具効率	75 %	天井	80 %				70 %				50 %				30 %				0 %	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %	
上方光束	1 %	床	10 %				10 %				10 %				10 %				0 %	
下方光束	74 %	室指数	照明率 (X0.01)																ZCM	
保守率	良 中 否	0.67	0.6	4.4	3.5	2.9	2.5	4.3	3.5	2.9	2.5	4.1	3.4	2.9	2.5	3.9	3.3	2.8	2.5	2.4
		0.63	0.8	5.2	4.4	3.9	3.5	5.1	4.4	3.8	3.5	4.9	4.3	3.8	3.4	4.7	4.2	3.7	3.4	3.3
		0.56	1.0	5.8	5.0	4.5	4.1	5.6	5.0	4.5	4.1	5.4	4.9	4.4	4.1	5.3	4.8	4.4	4.1	3.9
			1.25	6.2	5.6	5.1	4.8	6.1	5.5	5.1	4.8	5.9	5.4	5.0	4.7	5.7	5.3	5.0	4.7	4.5
下方投影面積		1.5	6.5	6.0	5.6	5.2	6.4	5.9	5.5	5.2	6.2	5.8	5.4	5.1	6.0	5.7	5.3	5.1	4.9	
等価発光面積		2.0	6.9	6.5	6.1	5.8	6.8	6.4	6.1	5.8	6.6	6.3	6.0	5.7	6.4	6.1	5.9	5.7	5.5	
取付高さ	器具間隔最大限		2.5	7.2	6.8	6.5	6.2	7.1	6.7	6.4	6.2	6.9	6.6	6.3	6.1	6.7	6.4	6.2	6.0	5.9
	横方向 (A)	縦方向 (B)	3.0	7.3	7.0	6.7	6.5	7.2	6.9	6.7	6.4	7.0	6.8	6.6	6.4	6.8	6.6	6.4	6.3	6.1
Hm	1.64 Hm	1.64 Hm	4.0	7.5	7.3	7.1	6.9	7.4	7.2	7.0	6.8	7.2	7.0	6.9	6.7	7.0	6.9	6.7	6.6	6.4
			5.0	7.6	7.4	7.2	7.1	7.5	7.3	7.2	7.0	7.3	7.2	7.0	6.9	7.2	7.0	6.9	6.8	6.6
			7.0	7.8	7.6	7.5	7.3	7.7	7.5	7.4	7.3	7.5	7.4	7.3	7.2	7.3	7.2	7.1	7.0	6.8
			10.0	7.9	7.7	7.6	7.6	7.8	7.7	7.6	7.5	7.6	7.5	7.4	7.3	7.4	7.3	7.3	7.2	7.0

