

屋内照明器具特性	
品番(品名)	LGB15125BK
光源	LDA7L-G/Z60E/S/W/2 × 1 810.0 l m
管理番号	K0155055(0)DB1
BZ分類	BZ8

器具効率	84%	反射率	天井	80%				70%				50%				30%				0%
			壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
上方光束	35%	室指数	床	10%				10%				10%				10%				0%
下方光束	49%		照明率 (X0.01)																ZCM	
保守率	良 0.63	0.6	0.6	3.8	2.7	2.1	1.6	3.5	2.5	1.9	1.5	3.0	2.2	1.7	1.3	2.5	1.8	1.4	1.1	7
	中 0.6		0.8	4.5	3.5	2.7	2.2	4.2	3.2	2.6	2.1	3.5	2.8	2.2	1.8	2.9	2.3	1.9	1.6	1.1
	否 0.56		1.0	5.0	4.0	3.3	2.7	4.6	3.7	3.1	2.6	3.9	3.2	2.7	2.2	3.3	2.7	2.3	1.9	1.3
			1.25	5.5	4.5	3.8	3.3	5.1	4.2	3.6	3.1	4.3	3.6	3.1	2.7	3.6	3.1	2.6	2.3	1.6
下方投影面積	cm ²	1.5	5.8	4.9	4.2	3.7	5.4	4.6	4.0	3.5	4.6	4.0	3.5	3.0	3.8	3.3	2.9	2.6	1.9	
等価発光面積		2.0	6.3	5.5	4.9	4.4	5.8	5.2	4.6	4.1	5.0	4.4	4.0	3.6	4.2	3.8	3.4	3.1	2.3	
取付高さ		器具間隔最大限		2.5	6.6	5.9	5.3	4.9	6.1	5.5	5.0	4.6	5.3	4.8	4.4	4.0	4.4	4.1	3.7	2.5
Hm		横方向(A)	縦方向(B)	3.0	6.8	6.2	5.7	5.2	6.4	5.8	5.3	4.9	5.5	5.0	4.7	4.3	4.6	4.3	4.0	2.8
Hm	1.84Hm	1.83Hm	4.0	7.1	6.6	6.2	5.8	6.7	6.2	5.8	5.4	5.8	5.4	5.1	4.8	4.9	4.6	4.4	3.1	
			5.0	7.3	6.9	6.5	6.1	6.8	6.5	6.1	5.8	5.9	5.6	5.3	5.1	5.1	4.8	4.6	3.3	
			7.0	7.6	7.2	6.9	6.6	7.1	6.8	6.5	6.2	6.2	5.9	5.7	5.5	5.3	5.1	4.9	3.6	
			10.0	7.7	7.5	7.2	7.0	7.3	7.0	6.8	6.6	6.4	6.2	6.0	5.8	5.5	5.3	5.2	3.9	

