

屋内照明器具特性

品番 (品名)	LGB16021YZ														
光源	LDA4L-H-E17/E/S/W/2 ×1 440.0 1 m														
管理番号	K0170216(0)DR1														
BZ分類	BZ5/2.8/BZ4														

器具効率	96%	天井	80%				70%				50%				30%				0%		
			反射率	壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
				床	10%				10%				10%				10%				0%
上方光束	0%	室指数	照明率 (X0.01)																ZCM		
下方光束	96%																				
保守率	良 中 否 0.67 0.63 0.56	0.6	54	42	34	29	52	41	34	29	50	40	33	29	48	39	33	28	27		
		0.8	64	52	45	39	62	52	44	39	59	50	44	39	57	49	43	39	36		
		1.0	70	60	52	47	69	59	52	46	66	57	51	46	63	56	50	46	44		
		1.25	76	67	60	54	75	66	59	54	72	64	58	54	69	62	57	53	51		
下方投影面積	c m ²	1.5	80	72	65	60	79	71	65	60	76	69	64	59	73	67	63	59	56		
		2.0	86	79	73	68	84	78	72	68	81	76	71	67	79	74	70	66	64		
取付高さ	器具間隔最大限		2.5	89	83	78	74	88	82	78	74	85	80	76	73	82	78	75	72	69	
	横方向 (A)	縦方向 (B)	3.0	92	87	82	78	90	85	81	78	87	83	80	77	85	81	78	76	73	
H m	1.33 H m	1.33 H m	4.0	95	91	87	84	93	90	86	83	91	87	85	82	88	85	83	81	78	
			5.0	97	93	90	87	95	92	89	87	93	90	88	85	90	88	86	84	81	
			7.0	99	96	94	92	97	95	93	91	95	93	91	89	92	91	89	88	85	
			10.0	100	98	97	95	99	97	96	94	96	95	94	93	94	93	92	91	88	

