

屋内照明器具特性		
品番 (品名)	LGB15388	
光源	LDA6GE17 / KU / DN / S / W_6200K ×1	510.0 lm
管理番号	K0145820 (0) DB1	
BZ分類	BZ5 / 1.1 / BZ6	

器具効率	86%	天井	80%				70%				50%				30%				0%	
	上方光束 29%		下方光束 57%	壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10
室指数	照明率 (X0.01)																			ZCM
保守率	良	0.67	0.6	4.4	3.4	2.8	2.3	4.2	3.2	2.7	2.2	3.7	2.9	2.4	2.1	3.3	2.6	2.2	1.9	1.6
	中	0.63	0.8	5.1	4.2	3.5	3.0	4.8	3.9	3.3	2.9	4.3	3.6	3.0	2.7	3.8	3.2	2.8	2.4	2.0
	否	0.56	1.0	5.6	4.7	4.0	3.5	5.3	4.5	3.8	3.4	4.7	4.0	3.5	3.1	4.1	3.6	3.2	2.8	2.3
	下方投影面積	c m ²		1.25	6.1	5.2	4.6	4.0	5.7	4.9	4.3	3.9	5.1	4.4	3.9	3.5	4.4	3.9	3.5	3.2
等価発光面積	c m ²		1.5	6.4	5.6	5.0	4.5	6.0	5.3	4.7	4.3	5.3	4.8	4.3	3.9	4.7	4.2	3.8	3.5	2.9
	c m ²		2.0	6.9	6.2	5.6	5.1	6.5	5.8	5.3	4.9	5.7	5.2	4.8	4.4	5.0	4.6	4.3	4.0	3.3
取付高さ	器具間隔最大限		2.5	7.2	6.5	6.0	5.6	6.7	6.2	5.7	5.3	6.0	5.5	5.2	4.8	5.3	4.9	4.6	4.3	3.6
	横方向 (A)	縦方向 (B)	3.0	7.4	6.8	6.3	5.9	7.0	6.5	6.0	5.6	6.2	5.8	5.4	5.1	5.5	5.1	4.9	4.6	3.8
H _m	1.12 H _m	1.12 H _m	4.0	7.6	7.2	6.8	6.4	7.2	6.8	6.4	6.1	6.4	6.1	5.8	5.5	5.7	5.4	5.2	5.0	4.1
			5.0	7.8	7.4	7.1	6.7	7.4	7.0	6.7	6.4	6.6	6.3	6.1	5.8	5.9	5.6	5.4	5.2	4.3
			7.0	8.0	7.7	7.4	7.2	7.6	7.3	7.1	6.8	6.8	6.6	6.4	6.2	6.1	5.9	5.7	5.6	4.6
			10.0	8.2	8.0	7.7	7.5	7.8	7.6	7.4	7.2	7.0	6.8	6.7	6.5	6.2	6.1	6.0	5.8	4.9

