

屋内照明器具特性

品番 (品名)	LGB15492															
光源	LDA7L-G/D/S/K6 ×1 810.0 lm															
管理番号	K0168262(0)DB1															
BZ分類	BZ2/2.3/BZ3															

器具効率	27%	天井	80%				70%				50%				30%				0%		
			反射率	壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
				床	10%				10%				10%				10%				0%
上方光束	3%	室指数	照明率 (X0.01)																ZCM		
下方光束	24%																				
保守率	良 中 否 0.67 0.63 0.56	0.6	18	15	14	12	17	15	13	12	16	14	13	12	16	14	13	12	11		
		0.8	20	18	16	15	20	17	16	15	19	17	15	14	18	16	15	14	13		
		1.0	22	19	18	17	21	19	17	16	20	18	17	16	19	17	16	16	15		
		1.25	23	21	19	18	22	20	19	18	21	20	18	17	20	19	18	17	16		
下方投影面積	c m ²	1.5	24	22	21	19	23	21	20	19	22	20	19	19	21	20	19	18	17		
		2.0	25	23	22	21	24	23	22	21	23	22	21	20	22	21	20	19	18		
取付高さ	器具間隔最大限		2.5	26	24	23	22	25	24	23	22	24	23	22	21	22	22	21	20	19	
	横方向 (A)	縦方向 (B)	3.0	26	25	24	23	25	24	23	23	24	23	22	22	23	22	22	21	20	
H m	1.11H m	1.11H m	4.0	27	26	25	24	26	25	24	24	25	24	23	23	23	23	22	22	20	
			5.0	27	26	26	25	26	26	25	25	25	24	24	24	24	23	23	23	23	21
			7.0	27	27	26	26	27	26	26	25	25	25	25	24	24	24	23	23	22	
			10.0	28	27	27	27	27	27	26	26	26	25	25	25	24	24	24	24	22	

