

屋内照明器具特性

品番 (品名)	LGB16236	
光源	LED3500_70_430 x1	430.0 lm
管理番号	K0151377(0)DB1	
BZ分類	BZ5	

器具効率	100%	天井	80%				70%				50%				30%				0%		
	上方光束 0%		下方光束 100%	反射率	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
室指数	照明率 (X0.01)																				ZCM
保守率	良	0.63	0.6	56	44	36	31	55	44	36	31	53	42	35	31	50	41	35	30	28	
	中	0.6	0.8	67	55	47	41	65	54	47	41	62	53	46	41	60	51	45	41	38	
	否	0.56	1.0	73	62	55	49	72	62	54	49	69	60	53	48	66	58	52	48	46	
			1.25	79	69	62	56	78	68	62	56	74	67	61	56	72	65	60	55	53	
下方投影面積	cm ²		1.5	83	75	68	62	82	73	67	62	79	71	66	61	76	70	65	61	58	
等価発光面積	cm ²		2.0	89	82	76	71	87	81	75	70	84	78	73	69	81	76	72	68	66	
取付高さ	器具間隔最大限		2.5	93	86	81	76	91	85	80	76	88	83	79	75	85	81	77	74	71	
	横方向 (A)	縦方向 (B)	3.0	95	90	85	81	94	88	84	80	90	86	82	79	88	84	81	78	75	
Hm	1.29Hm	1.29Hm	4.0	98	94	90	86	97	93	89	86	94	90	87	84	91	88	86	83	80	
			5.0	100	97	93	90	99	95	92	89	96	93	90	88	93	91	89	87	84	
			7.0	102	100	97	95	101	98	96	94	98	96	94	92	96	94	92	91	88	
			10.0	104	102	100	98	103	101	99	98	100	99	97	96	98	96	95	94	91	

