

屋内照明器具特性	
品番 (品名)	LGB19305K
光源	LDA8L-G / K60E / S / W ×2 810.0 lm
管理番号	K0160392 (0) DR1
BZ分類	BZ5 / 1.4 / BZ6

器具効率	56%	天井	80%				70%				50%				30%				0%		
	上方光束		19%	壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
	下方光束		37%		床	10%				10%				10%				10%			
室指数	照明率 (×0.01)																			ZCM	
保守率	良	0.67	0.6	2.8	2.2	1.7	1.4	2.7	2.1	1.7	1.4	2.3	1.8	1.5	1.3	2.0	1.6	1.4	1.2	0.9	
	中	0.63	0.8	3.3	2.7	2.2	1.9	3.1	2.5	2.1	1.8	2.7	2.3	1.9	1.7	2.4	2.0	1.8	1.5	1.3	
	否	0.56	1.0	3.6	3.0	2.6	2.3	3.4	2.9	2.5	2.2	3.0	2.6	2.3	2.0	2.6	2.3	2.0	1.8	1.5	
			1.25	3.9	3.4	3.0	2.6	3.7	3.2	2.8	2.5	3.3	2.9	2.5	2.3	2.9	2.5	2.3	2.1	1.7	
下方投影面積	c m ²		1.5	4.2	3.6	3.2	2.9	3.9	3.4	3.1	2.8	3.4	3.1	2.8	2.5	3.0	2.7	2.5	2.3	1.9	
	等価発光面積		c m ²	2.0	4.4	4.0	3.6	3.3	4.2	3.8	3.4	3.2	3.7	3.4	3.1	2.9	3.2	3.0	2.8	2.6	2.1
取付高さ	器具間隔最大限		2.5	4.6	4.2	3.9	3.6	4.4	4.0	3.7	3.4	3.9	3.6	3.3	3.1	3.4	3.2	3.0	2.8	2.3	
	横方向 (A)	縦方向 (B)	3.0	4.8	4.4	4.1	3.8	4.5	4.2	3.9	3.7	4.0	3.7	3.5	3.3	3.5	3.3	3.1	3.0	2.4	
H m	1.33 H m	1.33 H m	4.0	4.9	4.6	4.4	4.1	4.7	4.4	4.2	4.0	4.1	3.9	3.7	3.6	3.7	3.5	3.3	3.2	2.6	
			5.0	5.0	4.8	4.6	4.4	4.8	4.5	4.3	4.2	4.3	4.1	3.9	3.8	3.8	3.6	3.5	3.4	2.8	
			7.0	5.2	5.0	4.8	4.6	4.9	4.7	4.6	4.4	4.4	4.2	4.1	4.0	3.9	3.8	3.7	3.6	2.9	
			10.0	5.3	5.1	5.0	4.9	5.0	4.9	4.8	4.6	4.5	4.4	4.3	4.2	4.0	3.9	3.8	3.7	3.1	

