

| | |
|----------|-----------------------------|
| 屋内照明器具特性 | |
| 品番 (品名) | LGB19229W |
| 光源 | LED3500_70_470 x2 470.0 l m |
| 管理番号 | K0161572(0)DB1 |
| BZ分類 | BZ8/0.7/BZ7 |

| | | | | | | | | | | | | | | | | | | | | |
|--------|---------------------------|----------|---------------|----|----|----|-----|----|----|----|-----|----|----|----|-----|----|----|----|-----|----|
| 器具効率 | 101% | 天井 | 80% | | | | 70% | | | | 50% | | | | 30% | | | | 0% | |
| | | 壁 | 70 | 50 | 30 | 10 | 70 | 50 | 30 | 10 | 70 | 50 | 30 | 10 | 70 | 50 | 30 | 10 | 0% | |
| 上方光束 | 38% | 床 | 10% | | | | 10% | | | | 10% | | | | 10% | | | | 0% | |
| 下方光束 | 63% | 室指数 | 照明率 (X0.01) | | | | | | | | | | | | | | | | ZCM | |
| 保守率 | 良 0.63 中 0.6 否 0.56 | 0.6 | 47 | 34 | 26 | 20 | 43 | 32 | 24 | 19 | 37 | 28 | 21 | 17 | 32 | 24 | 19 | 15 | 10 | |
| | | 0.8 | 55 | 43 | 34 | 28 | 51 | 40 | 32 | 26 | 44 | 35 | 28 | 23 | 37 | 30 | 25 | 21 | 15 | |
| | | 1.0 | 61 | 49 | 40 | 34 | 57 | 46 | 38 | 32 | 49 | 40 | 34 | 29 | 42 | 35 | 29 | 25 | 18 | |
| | | 1.25 | 67 | 56 | 47 | 40 | 62 | 52 | 44 | 38 | 54 | 45 | 39 | 34 | 46 | 39 | 34 | 30 | 22 | |
| 下方投影面積 | c m ² | 1.5 | 71 | 60 | 52 | 46 | 66 | 57 | 49 | 43 | 57 | 49 | 43 | 38 | 49 | 43 | 38 | 34 | 25 | |
| | | 2.0 | 77 | 67 | 60 | 54 | 72 | 63 | 57 | 51 | 62 | 55 | 50 | 45 | 53 | 48 | 44 | 40 | 30 | |
| 取付高さ | 器具間隔最大限 | | 2.5 | 80 | 72 | 65 | 59 | 75 | 68 | 62 | 56 | 65 | 60 | 54 | 50 | 56 | 52 | 48 | 44 | 34 |
| | 横方向 (A) | 縦方向 (B) | 3.0 | 83 | 76 | 69 | 64 | 78 | 71 | 66 | 61 | 68 | 63 | 58 | 54 | 59 | 54 | 51 | 47 | 37 |
| H m | 1.49 H m | 1.49 H m | 4.0 | 87 | 81 | 75 | 70 | 81 | 76 | 71 | 67 | 71 | 67 | 63 | 59 | 62 | 58 | 55 | 52 | 41 |
| | | | 5.0 | 89 | 84 | 79 | 75 | 84 | 79 | 75 | 71 | 74 | 70 | 66 | 63 | 64 | 61 | 58 | 56 | 44 |
| | | | 7.0 | 92 | 88 | 84 | 80 | 87 | 83 | 79 | 76 | 76 | 73 | 71 | 68 | 67 | 64 | 62 | 60 | 48 |
| | | | 10.0 | 94 | 91 | 88 | 85 | 89 | 86 | 83 | 81 | 79 | 76 | 74 | 72 | 69 | 67 | 65 | 64 | 51 |

