

|          |                              |
|----------|------------------------------|
| 屋内照明器具特性 |                              |
| 品番(品名)   | LGB19271WK                   |
| 光源       | LDA7L-G/Z60E/S/W/2×3 810.0lm |
| 管理番号     | K0140274(0)DB1               |
| BZ分類     | BZ8                          |

|        |         |                 |             |     |    |    |     |     |    |    |     |     |    |    |     |     |    |    |     |    |
|--------|---------|-----------------|-------------|-----|----|----|-----|-----|----|----|-----|-----|----|----|-----|-----|----|----|-----|----|
| 器具効率   | 90%     | 天井              | 80%         |     |    |    | 70% |     |    |    | 50% |     |    |    | 30% |     |    |    | 0%  |    |
|        |         |                 | 壁           | 70  | 50 | 30 | 10  | 70  | 50 | 30 | 10  | 70  | 50 | 30 | 10  | 70  | 50 | 30 | 10  | 0% |
| 上方光束   | 40%     | 反射率             | 10%         |     |    |    | 10% |     |    |    | 10% |     |    |    | 10% |     |    |    | 0%  |    |
| 下方光束   | 50%     |                 | 床           | 10% |    |    |     | 10% |    |    |     | 10% |    |    |     | 10% |    |    |     | 0% |
|        |         | 室指数             | 照明率 (X0.01) |     |    |    |     |     |    |    |     |     |    |    |     |     |    |    | ZCM |    |
| 保守率    | 良       | 0.63            | 0.6         | 41  | 30 | 22 | 17  | 38  | 27 | 21 | 16  | 31  | 23 | 18 | 14  | 26  | 19 | 15 | 11  | 7  |
|        | 中       | 0.6             | 0.8         | 48  | 37 | 30 | 24  | 44  | 34 | 27 | 22  | 37  | 29 | 24 | 19  | 30  | 24 | 20 | 16  | 10 |
|        | 否       | 0.56            | 1.0         | 54  | 43 | 35 | 29  | 49  | 40 | 33 | 27  | 41  | 34 | 28 | 24  | 34  | 28 | 23 | 20  | 13 |
|        |         |                 | 1.25        | 59  | 48 | 41 | 35  | 54  | 45 | 38 | 33  | 45  | 38 | 33 | 28  | 37  | 32 | 27 | 24  | 16 |
| 下方投影面積 |         | cm <sup>2</sup> | 1.5         | 62  | 53 | 45 | 40  | 57  | 49 | 42 | 37  | 48  | 42 | 36 | 32  | 40  | 35 | 30 | 27  | 18 |
| 等価発光面積 |         | cm <sup>2</sup> | 2.0         | 67  | 59 | 52 | 47  | 62  | 55 | 49 | 44  | 52  | 47 | 42 | 38  | 43  | 39 | 35 | 32  | 22 |
| 取付高さ   | 器具間隔最大限 |                 | 2.5         | 71  | 63 | 57 | 52  | 65  | 59 | 53 | 48  | 55  | 50 | 46 | 42  | 46  | 42 | 38 | 35  | 25 |
|        | 横方向(A)  | 縦方向(B)          | 3.0         | 73  | 66 | 61 | 56  | 68  | 62 | 57 | 52  | 57  | 53 | 49 | 45  | 48  | 44 | 41 | 38  | 27 |
| Hm     | 1.55Hm  | 1.29Hm          | 4.0         | 76  | 71 | 66 | 61  | 71  | 66 | 61 | 57  | 60  | 56 | 53 | 50  | 51  | 48 | 45 | 42  | 31 |
|        |         |                 | 5.0         | 78  | 73 | 69 | 65  | 73  | 68 | 65 | 61  | 62  | 59 | 56 | 53  | 52  | 50 | 47 | 45  | 33 |
|        |         |                 | 7.0         | 81  | 77 | 74 | 70  | 75  | 72 | 69 | 66  | 65  | 62 | 60 | 57  | 55  | 53 | 51 | 49  | 36 |
|        |         |                 | 10.0        | 83  | 80 | 77 | 75  | 77  | 75 | 72 | 70  | 67  | 65 | 63 | 61  | 57  | 55 | 54 | 52  | 39 |

