

屋内照明器具特性	
品番 (品名)	LGB19471
光源	LDA8L-G/K60E/S/W ×4 810.0 lm
管理番号	K0153870(0)DB1
BZ分類	BZ6/0.9/BZ5

器具効率	74%	反射率	天井	80%				70%				50%				30%				0%	
	上方光束		20%	壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
	下方光束		54%	床	10%				10%				10%				10%				0%
		室指数	照明率 (X0.01)																ZCM		
保守率	良	0.67	0.6	37	28	22	18	35	27	21	18	32	25	20	16	28	22	18	15	12	
	中	0.63	0.8	45	36	30	26	42	34	29	25	38	31	27	23	34	29	25	22	18	
	否	0.56	1.0	50	41	36	31	47	40	34	30	42	36	32	28	38	33	29	26	22	
			1.25	54	47	41	37	51	45	40	36	46	41	37	33	42	37	34	31	26	
下方投影面積			1.5	57	50	45	41	54	48	44	40	49	44	40	37	44	40	37	34	29	
	等価発光面積		2.0	62	56	51	47	59	54	49	46	53	49	46	43	48	45	42	39	34	
取付高さ	器具間隔最大限		2.5	64	59	55	52	61	57	53	50	56	52	49	46	50	48	45	43	37	
	横方向 (A)	縦方向 (B)	3.0	66	62	58	55	63	59	56	53	57	54	52	49	52	50	48	46	40	
Hm	1.68Hm	1.68Hm	4.0	69	65	62	60	66	63	60	57	60	57	55	53	54	52	51	49	43	
			5.0	70	67	65	62	67	64	62	60	61	59	57	56	56	54	53	51	45	
			7.0	72	70	68	66	69	67	65	63	63	61	60	59	57	56	55	54	47	
			10.0	73	72	70	69	70	69	67	66	64	63	62	61	59	58	57	56	49	

