

屋内照明器具特性	
品番 (品名)	LGB19561BK
光源	LDA7L-G/Z60E/S/W/2 ×5 810.0 l m
管理番号	K0140283(0)DB1
BZ分類	BZ8

器具効率	89%	反射率	天井	80%				70%				50%				30%				0%	
			壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%	
上方光束	39%	床	10%				10%				10%				10%				0%		
下方光束	50%	室指数	照明率 (X0.01)																ZCM		
保守率	良 0.63	0.6	4.0	2.9	2.2	1.7	3.7	2.7	2.0	1.6	3.1	2.3	1.8	1.4	2.6	1.9	1.5	1.1	7		
	中 0.6	0.8	4.8	3.7	2.9	2.4	4.4	3.4	2.7	2.2	3.7	2.9	2.3	1.9	3.0	2.4	2.0	1.6	1.1		
	否 0.56	1.0	5.3	4.2	3.5	2.9	4.9	3.9	3.2	2.7	4.1	3.3	2.8	2.3	3.4	2.8	2.3	2.0	1.3		
		1.25	5.8	4.8	4.0	3.5	5.3	4.5	3.8	3.2	4.5	3.8	3.2	2.8	3.7	3.2	2.7	2.4	1.6		
下方投影面積	cm <sup>2</sup>	1.5	6.2	5.2	4.5	3.9	5.7	4.8	4.2	3.7	4.8	4.1	3.6	3.2	4.0	3.5	3.0	2.7	1.9		
等価発光面積		2.0	6.7	5.8	5.2	4.6	6.2	5.4	4.8	4.3	5.2	4.6	4.2	3.7	4.3	3.9	3.5	3.2	2.3		
取付高さ		器具間隔最大限		2.5	7.0	6.3	5.7	5.1	6.5	5.8	5.3	4.8	5.5	5.0	4.5	4.2	4.6	4.2	3.9	3.5	2.5
Hm		横方向 (A)	縦方向 (B)	3.0	7.2	6.6	6.0	5.5	6.7	6.1	5.6	5.2	5.7	5.3	4.9	4.5	4.8	4.4	4.1	3.8	2.8
	1.68Hm	1.36Hm	4.0	7.5	7.0	6.5	6.1	7.0	6.5	6.1	5.7	6.0	5.6	5.3	5.0	5.1	4.8	4.5	4.2	3.1	
			5.0	7.7	7.3	6.9	6.5	7.2	6.8	6.4	6.1	6.2	5.9	5.6	5.3	5.2	5.0	4.7	4.5	3.4	
			7.0	8.0	7.6	7.3	7.0	7.5	7.1	6.8	6.5	6.4	6.2	5.9	5.7	5.5	5.3	5.1	4.9	3.7	
			10.0	8.2	7.9	7.6	7.4	7.7	7.4	7.2	6.9	6.6	6.4	6.2	6.1	5.7	5.5	5.4	5.2	3.9	

