

屋内照明器具特性																						
品番(品名)	LGB50125																					
光源	LED2700_70_380 ×1 380.0 lm																					
管理番号	K0138976(0)DB1																					
BZ分類	BZ1																					
器具効率	101%																					
上方光束	0%																					
下方光束	101%																					
反射率	天井	80%				70%				50%				30%				0%				
	壁 床	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
室指数	照明率 (X 0.01)																				ZCM	
保守率	良	0.63	0.6	0.56	0.6	82	75	70	68	81	74	70	67	79	74	70	67	78	73	70	67	66
	中	0.6			0.8	88	82	78	75	87	81	77	74	85	80	77	74	84	80	76	74	73
	否	0.56			1.0	92	86	82	79	91	86	82	79	89	85	81	79	87	84	81	78	77
下方投影面積		cm ²																				
	等価発光面積		cm ²																			
取付高さ	器具間隔最大限		2.5	102	99	97	94	101	98	96	94	99	97	95	93	97	95	93	92	90		
	横方向(A)	縦方向(B)	3.0	103	101	98	96	102	100	98	96	100	98	96	95	98	96	95	94	91		
Hm	0.45Hm	0.45Hm	4.0	105	103	101	99	104	102	100	99	101	100	98	97	99	98	97	96	94		
			5.0	106	104	102	101	104	103	102	101	102	101	100	99	100	99	98	97	95		
			7.0	107	105	104	103	105	104	103	102	103	102	101	101	100	100	99	98	96		
			10.0	107	106	106	105	106	105	104	104	103	103	102	102	101	101	100	99	98		

