

屋内照明器具特性

品番 (品名)	LGB50631															
光源	LED2700_70_1486 x1 1486.0 lm															
管理番号	K0146930(0)DB1															
BZ分類	BZ4															

器具効率	100%	天井	80%				70%				50%				30%				0%		
			反射率	壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
				床	10%				10%				10%				10%				0%
上方光束	0%	室指数	照明率 (X0.01) ZCM																		
下方光束	100%																				
保守率	良 中 否	0.67	0.6	5.9	4.7	3.9	3.4	5.7	4.6	3.9	3.4	5.5	4.5	3.9	3.4	5.3	4.4	3.8	3.4	3.2	
		0.63	0.8	6.9	5.8	5.0	4.5	6.7	5.7	5.0	4.5	6.5	5.6	4.9	4.5	6.2	5.5	4.9	4.4	4.2	
		0.56	1.0	7.6	6.5	5.8	5.3	7.4	6.5	5.8	5.2	7.1	6.3	5.7	5.2	6.9	6.2	5.6	5.2	5.0	
			1.25	8.1	7.2	6.6	6.0	8.0	7.1	6.5	6.0	7.7	7.0	6.4	5.9	7.4	6.8	6.3	5.9	5.7	
下方投影面積	c m ²	1.5	8.5	7.7	7.1	6.6	8.4	7.6	7.0	6.5	8.1	7.4	6.9	6.5	7.8	7.3	6.8	6.4	6.2		
		2.0	9.1	8.4	7.8	7.4	8.9	8.3	7.8	7.3	8.6	8.1	7.6	7.3	8.4	7.9	7.5	7.2	6.9		
取付高さ	器具間隔最大限		2.5	9.4	8.8	8.3	7.9	9.3	8.7	8.3	7.9	9.0	8.5	8.1	7.8	8.7	8.3	8.0	7.7	7.4	
	横方向 (A)	縦方向 (B)	3.0	9.6	9.1	8.7	8.3	9.5	9.0	8.6	8.3	9.2	8.8	8.5	8.2	8.9	8.6	8.3	8.1	7.8	
1.5m	1.87m	2.16m	4.0	9.9	9.5	9.2	8.9	9.8	9.4	9.1	8.8	9.5	9.2	8.9	8.7	9.3	9.0	8.8	8.5	8.3	
2	2.47	2.73	5.0	10.1	9.8	9.5	9.2	10.0	9.7	9.4	9.1	9.7	9.4	9.2	9.0	9.4	9.2	9.0	8.9	8.6	
2.5	3.08	3.32	7.0	10.3	10.1	9.8	9.6	10.2	10.0	9.7	9.6	9.9	9.7	9.6	9.4	9.7	9.5	9.4	9.2	8.9	
3	3.68	3.92	10.0	10.5	10.3	10.1	10.0	10.3	10.2	10.0	9.9	10.1	9.9	9.8	9.7	9.8	9.7	9.6	9.5	9.2	

